

Musa

Design by Note Design Studio.

Reference

7415.

Application

Wall Fixtures

Installation type

Surface mounted

Description

Musa, made from an aluminum base with a triple blown-glass opal diffuser, combines delicacy and subtlety. The base captures light as the small glass sphere transforms it into soft illumination. The wall lamp remains cool to the touch thanks to an innovative heat dissipation system.

Diffuser

Blown-glass diffuser

Materials

Diffuser: Blown-glass

Body: Aluminum

Wall plate: Steel

Finishes



7415-58 Matt salmon (NCS S 1010-Y50R)




7415-59 Mink (NCS S 2005-Y50R)



7415-93 White (RAL 9016)

Sketch



Electrical characteristics

1 x LED 4.5W 350mA

Total 4.5 W



VIBIA



Light source: 2700K CRI >90 449 lm 99 lm/W

Fixture: 356 lm 79 lm/W

Driver included: CC - Constant Current 350 mA 120V 50/60Hz

Electronic dimming: TRIAC/ ELV


Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Coordinate system : CG

Isolux : Isolux (Floor)

Maximum value : 82.62 cd/klm

Light position :

Light position : C=285.00 G=25.00

X=0.00m Y=0.00m Z=2.50m

Symmetry on the planes : Symmetrical planes

270-90

Certificates

