

MINI ECHO PENDANT

PRODUCT FEATURES

- Die-cast aluminum body
- Geometrically striking design and detail draws the eye in
- Available in contemporary finishes
- Optical grade pressed glass lens diffuses light beautifully
- Fully dimmable LED creates the desired ambiance in your special space
- Protected by a 1-year warranty



LAMPING

Includes low-voltage, 50 watt halogen bi-pin lamp or 6 watt, 361 delivered lumen 90 CRI 3000K, replaceable LED module. Dimmable with low-voltage or magnetic dimmer (based on transformer). Ships with six feet of field-cuttable cable.



ORDERING INFORMATION

| 700 | SYSTEM | ECP | COLOR | FINISH | LAMP |
|-----|--------------|-----|--------------|------------------|---|
| | FJ FREEJACK | | C CLEAR | Z ANTIQUE BRONZE | 12 VOLT HALOGEN (T20) |
| | MP MONOPOINT | | S SMOKE | C CHROME | -24 24 VOLT HALOGEN |
| | MO MONORAIL | | U STEEL BLUE | S SATIN NICKEL | -LEDS930 12 VOLT LED 90 CRI 3000K (T20/T24) |
| | | | | | -24 24 VOLT HALOGEN |

Note: MP includes 4" Round Flush Canopy. Note: MP includes 4 Round Flush Canopy. Chrome not offered on Monorail & Two-Circuit Monorail.

700 _____ ECP _____

JOB NAME _____


NOTES _____



MINI ECHO PENDANT

SPECIFICATIONS

| | |
|-------------------------------|-------------|
| PRIMARY MATERIAL | Metal |
| SHADE MATERIAL | Glass |
| NET WEIGHT | 1.3 lbs |
| HEIGHT | 7in |
| WIDTH | 4in |
| LENGTH | 4in |
| UP LIGHT / DOWN LIGHT / BOTH? | |
| WET LISTED | |
| DAMP LISTED | |
| DRY LISTED | |
| MIN. HANGING HEIGHT | 13.5in |
| MAX HANGING HEIGHT | 79.5in |
| SLOPED CEILING ADAPTABLE? | Yes 45° Max |
| GENERAL LISTING | ETL Listed |
| INCLUDES | |



LAMPING SPECIFICATIONS

| | LED LAMP | INTEGRATED LED | NON LED | NO LAMP |
|-----------------------------|-------------------------------|----------------|-------------------------------|---------|
| DELIVERED LUMENS | 361.0 | | 558 | |
| WATTS | 6 | | 50 | |
| MAX WATTAGE PER BULB | 50W | | 50W | |
| INPUT VOLTAGE/ DIMMING TYPE | 12V ELV, MLV 120V ELV, MLV | | 12V ELV, MLV 120V ELV, MLV | |
| CCT | 3000K | | 3000K | |
| CRI | 90 CRI | | 100 CRI | |
| LED LIFETIME | | | | |
| L70 | >30000 | | | |
| AVERAGE BULB HOURS | | | 2000 | |
| FIELD SERVICEABLE LED | | | | |
| LAMP BASE | GY 6.35 | | GY 6.35 | |
| LAMP SHAPE | T4 | | T4 | |
| LAMP INCLUDED? | True | | True | |
| WARRANTY** | 1 Year | | 1 Year | |

*Dimming information available at www.techlighting.com/Downloads#dimming
 ** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

| | Integrated LED | Replacement LED Lamp | No Lamp * |
|--|----------------|----------------------|-----------|
| This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8. | | Yes | |
| This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California. | | Yes | |

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

