:Fabbian

Olympic
F45G03A01
*Lorenzo Truant*

Fixture Type

Project Name

Dimensions

Ø31 7/16''

1 15/16''

Description
Wall/ceiling lamp with white painted aluminium structure and plastic material diffuser.

Voltage	**Dimmable**	**Specs**
120V/24V	0-10V	ETL Intertek DRY

Material
Aluminium - Plastic

Light source
LED 1x56W-120°
3000K (2700K delivered)
6000lm (3000 delivered lumens) Cri >90

Color
☐ White

Notes
277V Available

Other colors available
Check online www.fabbian.us

Included accessories
LED
0-10V Dimmable electronic driver

In the same family


Pendant   Multiple pendant

Weight Lamp
Net: 0 lb

Packaging
Gross weight: 0 lb
Volume: 0 ft³
Number of boxes:

Olympic F45

Other options

	code		electrification	technical info
	F45 G01 A	**01**	LED 120V/24V	ETL Intertek DRY
	F45 G01 A	**76**	x45W-120°	
			3000K (2700K delivered)	
			4500lm (2250 delivered lumens) Cri >90	
			0-10V Dimming	
	F45 G02 A	**01**	LED 120V/24V	ETL Intertek DRY
	F45 G02 A	**76**	1x45W-120°	
			2700K (2400K delivered)	
			4500lm (2250 delivered lumens) Cri >90	
			0-10V Dimming	

Ø23 9/16"   H 1 15/16"

	code		electrification	technical info
	F45 G03 A	**01**	LED 120V/24V	ETL Intertek DRY
	F45 G03 A	**76**	x56W-120°	
			3000K (2700K delivered)	
			6000lm (3000 delivered lumens) Cri >90	
			0-10V Dimming	
	F45 G04 A	**01**	LED 120V/24V	ETL Intertek DRY
	F45 G04 A	**76**	x56W-120°	
			2700K (2400K delivered)	
			6000lm (3000 delivered lumens) Cri >90	
			0-10V Dimming	

Ø31 7/16"   H 1 15/16"

	code		electrification	technical info
	F45 G05 A	**01**	LED 120V/24V	ETL Intertek DRY
	F45 G05 A	**76**	x76W-120°	
			3000K (2700K delivered)	
			8250lm (4125 delivered lumens) Cri >90	
			0-10V Dimming	
	F45 G06 A	**01**	LED 120V/24V	ETL Intertek DRY
	F45 G06 A	**76**	x76W-120°	
			2700K (2400K delivered)	
			8250lm (4125 delivered lumens) Cri >90	
			0-10V Dimming	

Ø43 1/4"   H 1 15/16"

⬚	**F45 G07 A 01** **F45 G07 A 76**	LED 120V/24V x98W-120° 3000K (2700K delivered) 10600lm (5300 delivered lumens) Cri >90 0-10V Dimming	ETL Intertek	DRY
	F45 G08 A 01 **F45 G08 A 76**	LED 120V/24V 1x98W-120° 2700K (2400K delivered) 10600lm (5300 delivered lumens) Cri >90 0-10V Dimming	ETL Intertek	DRY

H 1 15/16"
Ø55 1/16"