


CRIS

design: Roberto Mantovani




Supply current
 Courant d'alimentation
 Corriente de alimentación
500mA (V_f 8.7V)

Power
 Pouissance
 Potencia
4.5W



Photometric diagrams



CCT	Flux	CRI
2700K	540 lm	98+
3000K	600 lm	98+
3500K	610 lm	98+
4200K	620 lm	98+



Code Construction

Construction du code produit
 Construcción del código de producto

CR2 | X | XX | X |


CR2	X	Finishing	XX	Color Temp.	X	Beam angle
		Finitions Acabados		Température couleur Temperatura de color		Angle de faisceau Ángulo del haz
	1	White Blanc Blanco	27	2700K	S	18°
	2	Grey Gris	30	3000K	F	40°
	5	Black Noir Negro	35	3500K		
			42	4200K		
			CU	Custom		

Drivers

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



0-10V

FLEXA-60-PRO-CC-10V

Programmable 60W CC 0-10V Dimming
 Dimming Range: 0.1%
Min. 1/Max. 6 Fixtures per Driver

Phase

FLEXA-12-500-CC-ELV

12W 500mA Constant Current
 Dimming Range: 10%
Min. 1/Max. 2 Fixtures per Driver

FLEXA-23-500-CC-ELV

23W 500mA Constant Current
 Dimming Range: 10%
Min. 3/Max. 5 Fixtures per Driver

Lutron 2-Wire Phase

Hi-Lume 2-Wire Phase / 500mA Constant Current / Dimming Range: 1%

LTEA.1

Min. 1/Max. 2
 Fixtures per Driver

LTEA.2

Min. 2/Max. 4
 Fixtures per Driver

LTEA.3

Min. 4/Max. 6
 Fixtures per Driver

Lutron Ecosystem

LDE.1

Hi-Lume Ecosystem
 500mA Constant Current
 Dimming Range: 1%
Min. 2/Max. 3 Fixtures per Driver

LDE.2

Hi-Lume Ecosystem Premier
 500mA Constant Current
 Dimming Range: 1%
Min. 4/Max. 5 Fixtures per Driver

Optionals - Accessoires - Accesorios

CR0100

White
 Blanc
 Blanco

CR0200

Grey
 Gris

CR0500

Black
 Noir
 Negro

