



UPUL1160 - recessed
UPUL2160 - recessed
 Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminum. Available in several colors and sizes.

Typology: WALL, CEILING LAMP

Ratings


- Built in **LED** module
- CCT 3000 K
- Uplight (towards surface)
- Remote LED driver(s)
- Installs to ceiling or wall (requires recessed strain relief)
- Power supply 120/277V AC
- Switch mode: on-off
- Dimmable 1-10V LED driver (remote)
- Painted aluminum profile 23 x 23 mm
- Opalescent diffuser

UP UL 1160 h10 cm recessed
UP UL 2160 h25 cm recessed



Product code composition

U-LIGHT / h10 cm - 3 7/8" or h25 cm - 9 7/8" recessed ceiling lamp / DRIVER INCLUDED

h10cm lb 11.02 ft³ 9.88
 h25cm lb 11.9 ft³ 9.88




recessed canopy



10 or 25 cm - 3 7/8" or 9 7/8"

available heights



10 cm - 3 7/8" height

25 cm - 9 7/8" height

Type	Article	Colours	Version	Source
UP	UL 1160 LED (h10 cm)	AN anthracite grey	IN recessed canopy	LED 102W - diffused beam 3000K*, 2700K other CCT available upon request
	UL 2160 LED (h25 cm)	RU rust brown		



DRY LOCATION CRI90 120/277VAC



LED ~ 8575 lm 84 lm/W

hole Ø 4,5 cm - 1 3/4" / min depth 10 cm - 3 7/8"

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code UP UL1160LED RU IN



sound absorbing option - see page xxx

Available colors



AN
Anthracite grey



RU
Rust brown

CUSTOMER _____ NOTES _____

UPUL _ 160LED _ _ IN

Luminous flux for all built-in LED luminaires is shown at source level. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.