

UP UL 1 160
UP UL 2 160
 Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminum.
 Available in several colors and sizes.


Typology: WALL, CEILING LAMP

Ratings



- Built in **LED** module
- CCT 3000 K
- Uplight (towards surface)
- Installs over 4 in. octagonal J-box (support independently)
- Power supply 120/277V AC
- Switch mode: on-off
- Dimmable 1-10V LED driver*
- Painted aluminum profile 23 x 23 mm
- Opalescent diffuser

UP UL 1 160 h10 cm canopy
UP UL 2 160 h25 cm canopy


h10cm lb 20.28 ft³ 10.94
h25cm lb 21.16 ft³ 10.94




standard canopy



available heights



10 cm - 3 7/8" height



25 cm - 9 7/8" height

Product code composition

U-LIGHT / h10 cm - 3 7/8" or h25 cm - 9 7/8" ceiling lamp with canopy

Type	Article	Colours	Version	Source
UP	UL 1 160 LED (h10 cm)	AN anthracite grey	XX standard canopy	LED 125W - diffused beam 3000K*, 2700K other CCT available upon request
	UL 2 160 LED (h25 cm)	RU rust brown		

DRY LOCATION CRI90 120/277VAC **LED** ~ 8575 lm 69 lm/W

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code **UP UL2160LED AN XX**



sound absorbing option - see page xxx

Available colors



AN
Anthracite grey



RU
Rust brown

CUSTOMER _____ NOTES _____

UPUL _ 160LED _ _ XX

Luminous flux for all built-in LED luminaires is shown at source level.
 Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.