



## US LIAI G 4 Design by Sara Moroni

Collection consisting of metal suspended lamps. Available in several colours and sizes. Built-in dimmable LED light source.


Typology: suspended

### Ratings

- •Built in ED module
- •CCT 3000 K
- •optic ~40° beam
- ·Surface installation over holes
- •Supply voltage ~100-240V
- •Switch mode: on-off
- •Dimmable 0/1-10V

### US LIAI G 4

lb 13.37 ft3 6.334



Product code composition

#### LIAISON / DRIVER INCLUDED

LIAISON / DRIVER INCLUDED						
Туре	Article	Arch / Final & sphere finishes	Source	•		
US	LIAI G 4	NE black / NE black	LED	.ED 4 x 7.5W - optic ~ 4 3000K*, 2700K	10° beam	
		NE black / OO matt gold				
		OO mattgold / NE black				
e us Intertek	dimmable DR	Y LOCATION CRI>90 LED	~2684	lm* 89 lm/W*	100-240VAC	

example composition code US LIAIG4 OO NE LED

# Available colors



CUSTOMER\_\_\_\_\_NOTES\_\_\_\_\_USLIAIG4\_\_\_\_LED

NOTICE: Luminous flux (Im) and efficacy (Im/W) for all built in LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.