UKIYO – UP UKIYO 110 – technical sheet





UPUKIYO110Design by Manuel Vivian

Collection consisting of ceiling or wall lamps with metal frame and white removable, washable elastic mesh fabric covering. Available in several sizes. Screw fitting light source.

Typology: CEILING-WALL LAMP

Ratings

- •E26
- •Diffused
- •Surface installation over holes
- •Supply voltage 120 V AC
- •Switch mode: on-off
- ·Steel frame, painted

lb 6.61 ft³ 4.238

110cm - 43 1/4" 77//

55 cm - 21 5/8"

Fireproof covering composed of two overlapping elastic fabrics
Net composition: 80% polyamide,
20% elastane (spandex)
Fabric composition: 67% polyamide,
33% elastane (spandex)
Weight 405 gr/m²
Glow wire 750°C

Product code composition

UKIYO / fabric INCLUDED - application: both as ceiling or wall lamp

Туре	Article	Colours	Finish	Source	
UP	UKI 110	BC white	XX white metal	E26 [#]	3 x Max 17W LED or 3 x Max 26W fluo





DRY LOCATION

example composition code Of Oki 110 DO XX L20	example composition code	UP	UKI110	BC	XX	E26
---------------------------------------------------------	--------------------------	----	---------------	----	----	-----

for additional fabric please refer to our pricelist or contact our representatives

Available lampshade colors



BC White

UPUKI110BCXXE26

CUSTOMER____

NOTES

Luminous flux for all built-in LED luminaires is shown at source level.

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.