



USURBANM

Design by Dima Loginoff

Collection consisting of aluminum ceiling lamps and suspended lamps.

Available in several colors and sizes.


Typology: SUSPENSION LAMP

Ratings

- •Built in line voltage **LED** module
- •CCT 3000 K
- •Downlight
- •Installs over 4 in. octagonal J-box
- •Power supply 120V AC
- •Switch mode: on-off, dimmable ELV trailing edge phase cut
- •Aluminum body, painted
- Opalescent diffuser

US URBAN M

Ib 5.07 ft3 0.8827



Product code composition

URBAN / downward lighting onl

URBAN / downward lighting only									
Туре	Article	Colours		Finishing		Source			
US	URBAN M	вс	wrinkled white	xx		LED	15W - diffused beam 3000K*, 2700K, 4000K		
		BR	matt bronze						
		NI	matt nickel						
Intertek	DRY LOCATIO)N (CRI90 —	dimmable ELV TRAILING EDGE PHASE CUT	120V	AC LE I	~ 1350 lm* 90 lm,	/W	

example composition code US URBANM BR XX LED

Available colors







BR Matt bronze



NI Matt nickel

USURBANM__XXLED

CUSTOMER

NOTES

NOTICE:

Luminous flux for all LED luminaires is shown at source level.

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.