

Lotos

Adjustable Downlight 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	_

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R4ERAR	W 45°	930 3000K - 90	750	1050	WT White

Example: R4ERAR-W930-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

Shallow profile LED that is designed to fit in in furred down ceilings without sacrificing lumen output. Available in 4" or 6" recessed or 4" adjustable LED recessed.

FEATURES

- Multiple LED array for uniform illumination
- Rotatable multi-axis gimbal ring
- Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 -277 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-5% ,TRIAC: 100-5%

Rated Life: 50000 Hours

Mounting: Heavy gauge retention clips secures fixture to ceiling

Standards: ETL, cETL, Title 24 JA8-2019 Compliant, Energy Star 2.0

Wet Location Listed

Construction: Steel with frosted TIR lens




FINISHES:



White

LINE DRAWING:





Lotos

Adjustable Downlight 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R6ERAR	W 45°	930 3000K - 90	1320	1915	WT White

Example: R6ERAR-W930-WT

For custom requests please contact customs@waclighting.com

FEATURES

- Multiple LED array for uniform illumination
- · Rotatable multi-axis gimbal ring
- Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 -277 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-5% ,TRIAC: 100-5%

Rated Life: 50000 Hours

Mounting: Heavy gauge retention clips secures fixture to ceiling
Standards: ETL, CETL, Title 24 JA8-2019 Compliant, Energy Star 2.0

Wet Location Listed

Construction: Steel with frosted TIR lens




FINISHES:



White

LINE DRAWING:



R6ERAR-W930-WT