



UPUL1090 - recessed
UPUL2090 - recessed
 Design by Timo Ripatti

Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminum. Available in several colors and sizes.

Typology: WALL, CEILING LAMP

Ratings


- Built in **LED** module
- CCT 3000 K
- Uplight (towards surface)
- Remote LED driver(s)
- Installs to ceiling or wall (requires recessed strain relief)
- Power supply 120/277V AC
- Switch mode: on-off
- Dimmable 1-10V LED driver (remote)
- Painted aluminum profile 23 x 23 mm
- Opalescent diffuser

UP UL 1 090 h10 cm recessed
UP UL 2 090 h25 cm recessed



Product code composition

U-LIGHT / h10 cm - 3 7/8" or h25 cm - 9 7/8" recessed ceiling lamp / DRIVER INCLUDED


h10cm lb 5.95 ft³ 4.44
h25cm lb 6.83 ft³ 4.44



recessed canopy



available heights



| Type | Article | Colours | Version | Source |
|------|---------------------------------|--------------------|--------------------|---|
| UP | UL 1 090 LED (h10 cm) | AN anthracite grey | IN recessed canopy | LED 53.6W - diffused beam 3000K*, 2700K other CCT available upon request |
| | UL 2 090 LED (h25 cm) | RU rust brown | | |

DRY LOCATION CRI90 120/277VAC **LED** ~ 4904 lm 91 lm/W

hole Ø 4,5 cm - 1 3/4" / min depth 10 cm - 3 7/8"

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code **UP UL1090LED RU IN**



sound absorbing option - see page xxx

Available colors



AN
Anthracite grey

RU
Rust brown

UPUL _ 090LED _ _ IN

CUSTOMER _____ NOTES _____

Luminous flux for all built-in LED luminaires is shown at source level.
 Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.