



**US LIAI P 1**

Design by Sara Moroni

Collection consisting of metal suspended lamps.  
Available in several colors and sizes.  
Built-in dimmable LED light source.

Typology: suspended

Ratings


- Built in **LED** module
- CCT 3000 K
- optic ~40° beam
- Surface installation over holes
- Supply voltage ~100-240V
- Switch mode: on-off
- Dimmable 0/1-10V

**US LIAI P 1**

lb 3.89 ft³ 2.086

Product code composition

LIAISON / DRIVER INCLUDED



Type	Article	Arch / Final & sphere finishes	Source
US	LIAI P 1	NE black / NE black	LED 9W - optic ~ 40° beam 3000K*, 2700K
		NE black / OO matt gold	
		OO matt gold / NE black	



DRY LOCATION CRI>90 **LED** ~671 lm\* 75 lm/W\* 100-240VAC

example composition code US LIAI P 1 NE NE LED

Available colors



NE/NE  
Black/black

OO/NE  
Matt gold  
/black

NE/OO  
Black/ Matt  
gold

Customizable

USLIAIP1 \_ \_ \_ \_ LED

CUSTOMER \_\_\_\_\_

NOTES \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.