



US LIAI M 4 Design by Sara Moroni

Collection consisting of metal suspended lamps. Available in several colors and sizes. Built-in dimmable LED light source.


Typology: suspended

Ratings

- •Built in ED module
- •CCT 3000 K
- •optic ~40° beam
- ·Surface installation over holes
- •Supply voltage ~100-240V
- •Switch mode: on-off
- •Dimmable 0/1-10V

US LIAI P 4

lb 12.55 ft³ 4.222



Product code composition

LIAISON / DRIVER INCLUDED

LIAISON / DRIVER INCLUDED						
Туре	Article	Arch / Final & sphere finishes	Source	e		
US	LIAI P 4	NE black / NE black	4 x 7.5V 3000K	4 x 7.5W - optic ~ 3000K*, 2700K	40° beam	
		NE black / OO matt gold				
		OO matt gold / NE black				
ontertek o	dimmable DR	Y LOCATION CRI>90 LED	~2684	lm* 89 lm/W*	100-240VA	

USLIAIM4 _ _ _ LED



/black

gold

CUSTOMER_____NOTES____

NOTICE: Luminous flux (lm) and efficacy (lm/W) for all built in LED luminaires is based on nominal ratings of the LED sources. Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.

example composition code US LIAIP4 NE NE LED