


UMA

design: Roberto Mantovani




Supply current
 Courant d'alimentation
 Corriente de alimentación
350mA (V_i 2.9V)

Power
 Pouissance
 Potencia
1W



Photometric diagrams



CCT	Flux	CRI
2700K	81 lm	93
3000K	81 lm	93
3500K	100 lm	93
4200K	107 lm	93

Code Construction

Construction du code produit
 Construcción del código de producto

UM | X | X | 2 | XX


UM	X	Shape	Forma	Forme	X	Finishing	Finitions	Acabados	2	XX	Color Temp.	Température couleur	Temperatura de color
	1	Round	Rond	Redondo	1	White	Blanc	Blanco		27	2700K		
	2	Square	Carré	Cuadrado	2	Grey	Gris			30	3000K		
					3	Chrome	Cromo			35	3500K		
					4	Gold	Or	Oro		42	4200K		
					5	Black	Noir	Negro		CU	Custom		

Drivers

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



0-10V

FLEXA-60-PRO-CC-10V
 Programmable 60W CC 0-10V Dimming
 Dimming Range: 0.1%
Min. 1/Max. 18 Fixtures per Driver

Phase

FLEXA-12-350-CC-ELV
 12W 350mA Constant Current
 Dimming Range: 10%
Min. 2/Max. 7 Fixtures per Driver

FLEXA-16-350-CC-ELV
 16W 350mA Constant Current
 Dimming Range: 10%
Min. 7/Max. 14 Fixtures per Driver

Lutron 2-Wire Phase


LTEA.1
 Hi-Lume 2-Wire Phase
 350mA Constant Current
 Dimming Range: 1%
Min. 3/Max. 6 Fixtures per Driver

LTEA.2
 Hi-Lume 2-Wire Phase
 350mA Constant Current
 Dimming Range: 1%
Min. 6/Max. 13 Fixtures per Driver

Optionals - Accessoires - Accesorios

CS1005

Recessing box
 Boîtier d'encastrement
 Caja de empotrar



Lutron Ecosystem

LDE.1
 Hi-Lume Ecosystem
 350mA Constant Current
 Dimming Range: 1%
Min. 3/Max. 10 Fixtures per Driver

LDE.2
 Hi-Lume Ecosystem Premier
 350mA Constant Current
 Dimming Range: 1%
Min. 11/Max. 16 Fixtures per Driver