



## **UPMUS120 E26**

## Design by Sandro Santantonio

Collection consisting of ceiling or wall lamps, suspended lamps and table lamps with metal frame and removable, washable elastic fabric covering. Available in several colours and sizes. Screw fitting light source.


Typology: WALL, CEILING LAMP

## Ratings

- •E26
- Diffused light
- •Surface installation over holes
- Power supply 120V AC
- •Switch mode: on-off
- ·Steel frame, painted

# **UP MUS 120**

lb 15.43 ft3 10.948



Product code composition

MUSE / application: both as ceiling or wall lamp


| 2 |               |         |      |             |                   |        |  |  |
|---|---------------|---------|------|-------------|-------------------|--------|--|--|
|   | Туре          | Article | Colo | urs         | Finish            | Source |  |  |
|   | UP            | MUS120  | вс   | white       | XX white<br>metal | E26    | 1 x Max 10W LED or<br>1 x Max 15W fluo |  |
|   |               |         | AR   | orange      |                   |        |  |  |
|   |               |         | GI   | Yellow      |                   |        |  |  |
|   |               |         | МС   | Multi color |                   |        |  |  |
|   |               |         | FI   | Flower      |                   |        |  |  |
|   |               |         | ST   | Sticks      |                   |        |  |  |
|   | · Drylocation |         |      |             |                   |        |  |  |

## Silk stretch fabric

Comp. 84% polyester, 16% elastane (Spandex) for multicolour MC. Comp. 80% polyamide, 20% elastane (Spandex) for other colours.

Weight 170/190 gr/m² for multicolour MC. Weight 195/215 gr/m² for white BC. Weight 180/200 gr/m² for other colours.

Light fastness (ISO 105 B02) from 3 to 6 Glow wire 750°C for multicolour MC Glow wire 850°C for white BC / other colours.



example composition code UP MUS120 GI XX E26

## Available coloure



BC

White

AR\* Orange



GI\* Yellow



MC Multi color



**FI** Flower

ST Sticks

\*Upon request

CUSTOMER

NOTES

PLMUS120\_ \_XXE26

Luminous flux for all built-in LED luminaires is shown at source level.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.