



UPUL1180 - recessed
UPUL2180 - recessed
 Design by Timo Ripatti


Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.
 Available in several colours and sizes.
 Available with sound absorbing panel option.

Typology: WALL, CEILING LAMP

Ratings

- Built in **LED** module
- CCT 3000 K or 2700K
- Wallward light (wall), downlight or uplight (ceiling)
- Installs to ceiling or wall (requires recessed strain relief)
- Power supply 120-270Vac
- Switch mode: on-off
- Dimmable 1-10V LED driver (remote)
- Painted aluminium profile 23 x 23 mm
- Opalescent diffuser


h10cm lb 12,56 ft³ 21.26
 h25cm lb 13,44 ft³ 21.26



Product code composition

U-LIGHT / h10 cm or h25 cm recessed ceiling lamp / DRIVER INCLUDED

Type	Article	Colours	Version	Source
UP	UL 1 180 LED (h10 cm)	AN anthracite grey	IN recessed canopy	LED 123W - diffused beam 3000K*, 2700K
	UL 2 180 LED (h25 cm)	RU rust brown		



DRY LOCATION CRI90 120/277Vac **LED** 9800 lm* 88 lm/W



hole Ø 4,5 cm - 1 3/4" / min depth 10 cm - 3 7/8"

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code **UP | UL1180LED | RU | IN |**

-for optional drivers or dimming technology please refer to our pricelist or contact our representatives

-sound absorbing option upon request- for more information see www.axolight.eu/u-light/u-light-sound-absorbing.pdf



Available colors



AN
Anthracite grey

RU
Rust brown

Sound absorbing option upon request

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER _____ NOTES _____

UPUL _ 180LED _ _ IN

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.
 Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.