

UP UL 1 180
UP UL 2 180
 Design by Timo Ripatti


Collection consisting of wall lamps, ceiling lamps and suspended lamps in aluminium.
 Available in several colours and sizes.
 Available with sound absorbing panel option.

Typology: WALL, CEILING LAMP


Ratings

- Built in **LED** module
- CCT 3000K or 2700K
- Uplight (towards surface)
- Installs over 4 in. octagonal J-box (support independently)
- Power supply 120/277V AC
- Switch mode: on-off
- Dimmable 1-10V LED driver*
- Painted aluminum profile 23 x 23 mm
- Opalescent diffuser


h10cm lb 23,14 ft³ 21.97
 h25cm lb 24,5 ft³ 21.97



standard canopy



available heights



10 cm - 3 7/8" height



25 cm - 9 7/8" height

Product code composition

U-LIGHT / h10 cm or h25 cm ceiling lamp with canopy / DRIVER INCLUDED

Type	Article	Colours	Version	Source
UP	UL 1 180 LED (h10 cm)	AN anthracite grey	XX standard canopy	LED 153W - diffused beam 3000K*, 2700K
	UL 2 180 LED (h25 cm)	RU rust brown		



DRY LOCATION

CRI90

120/277VAc



LED

9800 lm* 88 lm/W

Application: both as ceiling (downlight or uplight mounting) or wall lamp (only wallward light).

example composition code | **UP** | **UL2180LED** | **AN** | **XX** |

* If multiple luminaires are being connected to same dimming circuit please consider that source current from power supply unit (LED driver) is 0.1mA

-sound absorbing option upon request- for more information see www.axolight.eu/u-light/u-light-sound-absorbing.pdf

Available colors



AN
Anthracite grey



RU
Rust brown



Sound absorbing option upon request

EELc (Energy Efficiency Label compatibility) contain built in LED lamps that cannot be changed: A, A+, A++

CUSTOMER _____ NOTES _____

UPUL _ 180LED _ _ XX

Luminous flux (lm) and efficacy (lm/W) for all built-in LED luminaires is based on nominal ratings of the LED sources.
 Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.