


ZOOM

design: Lapo Grassellini



Supply current
 Courant d'alimentation
 Corriente de alimentación
500mA (V_f 2.9V)

Power
 Pouissance
 Potencia
1.5W



Adjustable optics

Optique réglable
 Óptica ajustable

10-55°

CCT	Flux	CRI
2700K	128 lm	93
3000K	133 lm	93
3500K	143 lm	93
4200K	154 lm	93

Code Construction

Construction du code produit
 Construcción del código de producto

ZM1 | X | XX |


ZM1	X	Finishing Finitions Acabados	XX	Color Temp. Température couleur Temperatura de color	Adjustable optics Optique réglable Óptica ajustable
		2 Aluminum Aluminium Aluminio		27 2700K	10-55°
		5 Black Noir Negro		30 3000K	
		6 Bronze Bronze		35 3500K	
				42 4200K	
				CU Custom	

Drivers

Alimentateurs
 Alimentadores

Series wiring

Câblage en série
 Cableado en serie



0-10V

FLEXA-60-PRO-CC-10V

Programmable 60W CC 0-10V Dimming
 Dimming Range: 0.1%
Min. 1/Max. 18 Fixtures per Driver

Phase

FLEXA-12-500-CC-ELV

12W 500mA Constant Current
 Dimming Range: 10%
Min. 2/Max. 7 Fixtures per Driver


FLEXA-23-500-CC-ELV

23W 500mA Constant Current
 Dimming Range: 10%
Min. 7/Max. 14 Fixtures per Driver


Optionals - Accessoires - Accesorios

XP0011

Earth spike
 Piquet de terre
 Pico de la tierra



Base



XP0200

Aluminum
 Aluminium
 Aluminio

XP0500

Black
 Noir
 Negro

XP0600

Bronze
 Bronze

Lutron 2-Wire Phase

LTEA.1

Hi-Lume 2-Wire Phase
 500mA Constant Current
 Dimming Range: 1%
Min. 3/Max. 6 Fixtures per Driver

LTEA.2

Hi-Lume 2-Wire Phase
 500mA Constant Current
 Dimming Range: 1%
Min. 6/Max. 13 Fixtures per Driver

Lutron Ecosystem

LDE.1

Hi-Lume Ecosystem
 500mA Constant Current
 Dimming Range: 1%
Min. 3/Max. 10 Fixtures per Driver

LDE.2

Hi-Lume Ecosystem Premier
 500mA Constant Current
 Dimming Range: 1%
Min. 11/Max. 16 Fixtures per Driver

Note: cable cut to measure on request

Note: câble sur mesure disponible sur demande

Nota: cable a medida disponible a petición