

WAC LIGHTING

Corkscrew

Pendant 4CCT

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-39443 43"	2700K	BK Black	38 W	2862	1785
	3000K		38 W	2862	1785
	3500K		38 W	2862	1785
	4000K		38 W	2862	1785

Example: **PD-39443-40-BK**

For custom requests please contact customs@wacighting.com

DESCRIPTION

A playful band of light spirals around a linear bar. This looped structure delivers artful style along with a soft layer of multi-directional illumination.

FEATURES

- Low profile, adjustable powered aircraft cables for an ultra-clean look
- May be mounted on slope ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Rectangular canopy with minimal hardware
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp:	4000K,3500K,3000K,2700K
Input:	120-277V,50/60Hz
CRI:	90
Dimming:	ELV: 100-10% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Standards:	ETL, cETL Damp Location Listed
Construction:	Aluminum body, silicone diffuser




FINISHES:



Black

LINE DRAWING:



PD-39443