

Crescent

Wall Sconce 4CCT

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-25410 10"	2700K 3000K 3500K 4000K	AB Aged Brass	11 W 11 W 11 W 11 W	532 532 532 532	416 416 416 416

Example: WS-25410-40-AB

For custom requests please contact customs@waclighting.com

DESCRIPTION

Wax and wane. Like a crescent moon playing hide and seek with the stars and slipping softly through the sky. Clear, ribbed cast glass throws lovely illumination to the room, whilesubtle down light is delivered from this luminaire's solid canopy.

FEATURES

- Up and downward illumination
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4" \times 1.2" \times 0.5"
- ACLED driverless technology

SPECIFICATIONS

Color Temp: 4000K,3500K,3000K,2700K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-5%

Rated Life: 50000 Hours

Mounting: Can be mounted on wall vertically or upside down

Standards: ETL, cETL

Damp Location Listed

Construction: Aluminum body with ribbed acrylic diffuser




FINISHES:



Aged Brass

LINE DRAWING:



WS-25410