



PRODUCT DESCRIPTION

Smaller square profiles extend vertically with light casting both upward and downward. The scale of the product is designed to meet ADA requirements, while providing ample light for outdoor applications. Concealed within the frame, there is a range voltage 120-277V LED driver making this a great option for light commercial as well as residential applications.

MEASUREMENTS

DIMENSION : 2.5" W x 14.5" H x 3.5" Ext
 BACK PLATE : 4.5" W x 4.5" H x 7.25" HCO
 HANGING WEIGHT : 2.6 lb

LAMPING

INPUT VOLTAGE : 120-277V
 LUMENS : 1,400 Rated (1,120 Del.)
 BULB : 2 x 7W LED DC Integrated , 14W Total
 BULB INCLUDED : (Integrated)
 DIMMABLE : Triac, 0-10V
 CRI : 90 CRI
 COLOR_TEMP : 3000K
 LIGHTING_DIRECTION : Up & Down

FINISHES OPTION

 Black (BK)

MATERIAL

Aluminum, Glass

RATINGS

cETLus
 Wet Location
 ADA



ADDITIONAL

INSTALL UP/DOWN: Up
 RATED LIFE 25000 Hours
 OPERATING TEMPERATURE:
 -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com