

FARO


Design Oriano Favaretto

FARO PL P



Faro consists of two glasses harmoniously connected by a metal ring. The first glass, with a transparent colored finish, appears to be connected to the second white glass that hides the LED source. The light is diffused, uniform and non-dazzling. Available in two sizes, in both pendant and ceiling versions.

FARO PL P



TECHNICAL DATA:



LED 2700K DIM2	1x13W	120V/60HZ
LED 2700K DIM3	1x13W	120V/60HZ
LED 3000K DIM2	1x13W	120V/60HZ
LED 3000K DIM3	1x13W	120V/60HZ

CERTIFICATIONS:



Led 2700 K 13 W 37 V 2000 lm DIM2 Phase Cut
Led 2700 K 13 W 37 V 2000 lm DIM3 0-10V, Push
Led 3000 K 13 W 37 V 2000 lm DIM2 Phase Cut
Led 3000 K 13 W 37 V 2000 lm DIM3 0-10V, Push

VOLUME	Mc 0,1
GROSS WEIGHT	Kg 6
NET WEIGHT	Kg 4,2

download



SHADE FINISHING



ADBC

CRBC

TBBC

VABC

FRAME FINISHING




NEO

OTV

OTHER VERSION AVAILABLE

Click on the version to go to the web version of the product



FARO PL G