

# Revolve square

Our Recessed family has grown with a new range of adjustable downlights. The effortless design and high functionality of these fixtures are sure to make a welcome addition in any room.

**NEW** WET LOW-GLARE ENERGY STAR Intertek IC RATED JA8 CERTIFIED

30° SWIVEL/DIRECTIONAL AIR TIGHT

2700k 3000k 3500k 4000k 5000k COLOR TEMPERATURE



\*Models GBR35-DW , GBR04-DW, GBR06-DW only

Model	Size	Watts	Delivered lumens	CRI	Color °T	Standard voltage	Multi-voltage ⚡
<b>GBR35SQ-CC</b>	3.5"	12 W	860 lm	90	2700, 3000, 3500, 4000, 5000 K	120V, Triac dimming	MV: 120 / 277 / 347V, 0-10V dimming

**Specifications**

Every fixture includes a junction box with an integrated driver  
 Over 50,000 hours service life  
 Switch-selectable CCT: 2700 K/ 3000 K/3500 K/4000 K/5000 K  
 40° beam angle  
 30° tilting, 360° rotation  
 Cast aluminum construction  
 Suitable for wet locations  
 Refer to website for dimmer compatibility  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 5-year warranty

**Finish**

○ **WH** White

**Accessories**

**RFP-35**

Rough-in plate

**REC-CC-EXT8FT**

8-foot extension cable

**REC-CC-EXT20FT**

20-foot extension cable

**Multi-voltage ⚡**

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

**Note**

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

