

Horus

A versatile lighting solution with a flexible design for precise illumination, its gimbal mechanism allows users to easily adjust the light angle, making it ideal for residential or commercial settings. The compact 3-inch size is suitable for tight spaces, and the spotlight's focused beam makes it perfect for accent lighting or task-oriented applications.

NEW  DAMP  360° SWIVEL/DIRECTIONAL  ETL Intertek  IC RATED  AIR TIGHT

 2700k 3000k 3500k 4000k 5000k
COLOR TEMPERATURE



Model	Size	Watts	Delivered lumens	CRI	Color °T	Voltage
GSP3-CC	3"	12 W	950 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V

Specifications

Every fixture includes a junction box with an integrated driver
 Over 50,000 hours service life
 Switch-selectable CCT: 2700 K/3000 K/3500 K/4000 K/5000 K
 60° beam angle
 30° tilting, 360° rotation
 Cast aluminum construction
 Suitable for damp locations
 Refer to website for dimmer compatibility
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 5-year warranty

Finish

- **BK** Black
- **GD** Gold

Accessories

- RFP-23**
Rough-in plate
- GSP-CC-EXT8FT**
8-foot extension cable
- GSP-CC-EXT20FT**
20-foot extension cable

Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

