




SOSPENSIONE / SUSPENSION

MEETING SILENCE LEAF



alluminio, policarbonato
sospensione fonoassorbente
fascio di luce verso l'alto e
verso il basso



aluminium, polycarbonate
soundabsorbing suspension
lamp
beam of light up and down



ON-OFF - Rosone con driver incluso
ON-OFF - Canopy with driver included



	M 2700	W 3000	N 4000
Potenza/ Power	1x103.2W, 2x20.4W	1x103.2W, 2x20.4W	1x103.2W, 2x20.4W
Lumen	1x11008lm, 2x2176lm	1x12026lm, 2x2377lm	1x12246lm, 2x2421lm
CRI	>90	>90	>90
Alimentazione/ Supply	220Vac 50Hz	220Vac 50Hz	220Vac 50Hz





Articolo Item	Temperatura Temperature	°Optica °Optic	Rosone Canopy	Corpo Body
6361	M	02	-NE ■	-NG ■
RS08/02 (1Pz)	W			
6360 (1Pz)	N			

PUSH/1-10V/DALI - Rosone con driver incluso
PUSH/1-10V/DALI - Canopy with driver included



	M 2700	W 3000	N 4000
Potenza/ Power	1x103.2W, 2x20.4W	1x103.2W, 2x20.4W	1x103.2W, 2x20.4W
Lumen	1x11008lm, 2x2176lm	1x12026lm, 2x2377lm	1x12246lm, 2x2421lm
CRI	>90	>90	>90
Alimentazione/ Supply	220Vac 50Hz	220Vac 50Hz	220Vac 50Hz



Articolo Item	Temperatura Temperature	°Optica °Optic	Rosone Canopy	Corpo Body
6362	M	02	-NE ■	-NG ■
RS10/02 (1Pz)	W			
6360 (1Pz)	N			


Il codice prodotto si compone mettendo uno dopo l'altro, da sinistra a destra, i dati nelle colonne gialle, es: 1111M12-AA
The product code is created by putting in sequence the data under the yellow columns from left to right, e.g:1111M12-AA

PRELIMINARY

CASAMBI - Rosone con driver incluso
CASAMBI - Canopy with driver included



6362/01	M 2700	W 3000	N 4000
Potenza/ Power	1x103.2W, 2x20.4W	1x103.2W, 2x20.4W	1x103.2W, 2x20.4W
Lumen	1x11008lm, 2x2176lm	1x12026lm, 2x2377lm	1x12246lm, 2x2421lm
CRI	>90	>90	>90
Alimentazione/ Supply	220Vac 50Hz	220Vac 50Hz	220Vac 50Hz





Articolo Item	Temperatura Temperature	°Optica °Optic	Rosone Canopy	Corpo Body
6362/01	M	02	-NE ■	-NG ■
RS10/04 (1Pz)	W			
6360 (1Pz)	N			

2CH - PUSH/1-10V/DALI - Rosone con driver incluso
2CH - PUSH/1-10V/DALI - Canopy with driver included



6362/02	M 2700	W 3000	N 4000
Potenza/ Power	1x103.2W, 2x20.4W	1x103.2W, 2x20.4W	1x103.2W, 2x20.4W
Lumen	1x11008lm, 2x2176lm	1x12026lm, 2x2377lm	1x12246lm, 2x2421lm
CRI	>90	>90	>90
Alimentazione/ Supply	220Vac 50Hz	220Vac 50Hz	220Vac 50Hz



Articolo Item	Temperatura Temperature	°Optica °Optic	Rosone Canopy	Corpo Body
6362/02	M	02	-NE ■	-NG ■
RS10/06 (1Pz)	W			
6360 (1Pz)	N			


Il codice prodotto si compone mettendo uno dopo l'altro, da sinistra a destra, i dati nelle colonne gialle, es: 1111M12-AA
The product code is created by putting in sequence the data under the yellow columns from left to right, e.g:1111M12-AA

PRELIMINARY




Solo Corpo / Only Body

6360	M 2700	W 3000	N 4000
Potenza/ Power	1x103.2W, 2x20.4W	1x103.2W, 2x20.4W	1x103.2W, 2x20.4W
Lumen	1x11008lm, 2x2176lm	1x12026lm, 2x2377lm	1x12246lm, 2x2421lm
CRI	>90	>90	>90
Alimentazione/ Supply	24Vdc	24Vdc	24Vdc



Articolo Item	Temperatura Temperature	°Optica °Optic	Finitura Finish
6360	M	02	-NG ■
	W		
	N		



Rosoni con Driver incluso / Canopy with driver included

Articolo Item	Finitura Finish	Potenza Power
RS08/02	-NE ■	200
RS10/02	-NE ■	200
RS10/04	-NE ■	200
RS10/06	-NE ■	200

Additional details for RS10 series: PUSH | 1-10V | DALI

Kit Leaf



Solo per Sospensione Meeting
Only for Meeting Suspension

Articolo Item
230

