

# RGR series

When choosing a recessed fixture, eliminating glare is a priority. The unique positioning of the LED module in this series of downlights will meet that important need.

**NEW** WET LOW-GLARE ENERGY STAR IC RATED AIR TIGHT JA8 CERTIFIED

2700k 3000k 3500k 4000k 5000k  
COLOR TEMPERATURE

ETL Intertek



Model	Size	Watts	Delivered lumens	CRI	Color °T	Standard voltage	Multi-voltage ⚡
<b>RGR1-CC</b>	1"	6 W	500 lm	90	2700, 3000, 3500, 4000, 5000 K	120V, Triac dimming	MV: 120 / 277 / 347V, 0-10V dimming
<b>RGR2-CC</b>	2"	8 W	600 lm				
<b>RGR2HP-CC</b>	2"	15 W	1080 lm				
<b>RGR4-CC</b>	4"	14 W	1100 lm				
<b>RGR4HP-CC</b>	4"	20 W	1560 lm				
<b>RGR6-CC</b>	6"	20 W	1600 lm				

### Specifications

Every fixture includes a junction box with integrated dimmable driver  
 Regressed light source  
 Minimal heat emission  
 Aluminum construction  
 Switch-selectable CCT: 2700K/3000 K/3500 K/4000 K/5000 K  
 IC certification (suitable for direct contact with insulation)  
 Air-tight certified as per ASTM E283-04  
 40° beam angle  
 Suitable for wet locations  
 Refer to website for dimmer compatibility  
 Ideal operating temperature: -20° to 40° C  
 5-year warranty

### Finish

- **BK** Black
- **WH** White

### Accessories

- RFP-23**  
Rough-in plate for RGR2
- RFP-35**  
Rough-in plate for RGR4
- RFP-46**  
Rough-in plate for RGR6
- REC-CC-EXT8FT**  
8-foot extension cable
- REC-CC-EXT20FT**  
20-foot extension cable

### Multi-voltage ⚡

This product family offers multi-voltage drivers (120/277/347) that are dimmable using 0-10V dimming systems. Please note that longer lead times may apply for this option. Kindly reach out to your DALI representative for additional information and to confirm availability.

### Note

Other color temperatures, finishes, and voltage options are available but may require minimum order quantities (MOQs) and longer lead times. Please contact your DALI representative for more information.

