

# WAC LIGHTING

## Revels

### Outdoor Wall Sconce

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

| Model & Size  | Color Temp | Finish   | LED Watts | LED Lumens | Delivered Lumens |
|---------------|------------|----------|-----------|------------|------------------|
| WS-W13324 24" | 3000K      | BK Black | 13W       | 300        | 193              |
|               | 3500K      |          | 13W       | 300        | 193              |
|               | 4000K      |          | 13W       | 300        | 193              |

Example: **WS-W13324-40-BK**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

#### DESCRIPTION

Balanced with geometric precision. A slim bar of light glowing between the lines of a minimal profile.

#### FEATURES

- Illumination on both sides with acrylic diffuser
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- 3CCT switch installs in the junction box
- ACLED driverless technology
- 5 year warranty

#### SPECIFICATIONS

|               |  |
|---------------|--|
| Color Temp:   | 4000K,3500K,3000K                          |
| Input:        | 120 VAC,50/60Hz                            |
| CRI:          | 90   |
| Dimming:      | ELV: 100-10%                               |
| Rated Life:   | 54000 Hours                                |
| Mounting:     | Can be mounted on wall in all orientations |
| Standards:    | ETL, cETL,IP65<br>Wet Location Listed      |
| Construction: | Extruded aluminum body with PC diffuser    |



#### FINISHES:



Black

#### LINE DRAWING:



WS-W13324

# WAC LIGHTING

## Revels

### Outdoor Wall Sconce

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

| Model & Size  | Color Temp | Finish   | LED Watts | LED Lumens | Delivered Lumens |
|---------------|------------|----------|-----------|------------|------------------|
| WS-W13336 36" | 3000K      | BK Black | 17W       | 400        | 256              |
|               | 3500K      |          | 17W       | 400        | 256              |
|               | 4000K      |          | 17W       | 400        | 256              |

Example: **WS-W13336-40-BK**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

#### DESCRIPTION

Balanced with geometric precision. A slim bar of light glowing between the lines of a minimal profile.

#### FEATURES

- Illumination on both sides with acrylic diffuser
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- 3CCT switch installs in the junction box
- ACLED driverless technology
- 5 year warranty

#### SPECIFICATIONS

|               |  |
|---------------|--|
| Color Temp:   | 4000K,3500K,3000K                          |
| Input:        | 120 VAC,50/60Hz                            |
| CRI:          | 90   |
| Dimming:      | ELV: 100-10%                               |
| Rated Life:   | 54000 Hours                                |
| Mounting:     | Can be mounted on wall in all orientations |
| Standards:    | ETL, cETL,IP65<br>Wet Location Listed      |
| Construction: | Extruded aluminum body with PC diffuser    |




#### FINISHES:



Black

#### LINE DRAWING:



WS-W13336

# WAC LIGHTING

## Revels

### Outdoor Wall Sconce

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

| Model & Size  | Color Temp | Finish   | LED Watts | LED Lumens | Delivered Lumens |
|---------------|------------|----------|-----------|------------|------------------|
| WS-W13348 48" | 3000K      | BK Black | 24W       | 555        | 358              |
|               | 3500K      |          | 24W       | 555        | 358              |
|               | 4000K      |          | 24W       | 555        | 358              |

Example: **WS-W13348-40-BK**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

#### DESCRIPTION

Balanced with geometric precision. A slim bar of light glowing between the lines of a minimal profile.

#### FEATURES

- Illumination on both sides with acrylic diffuser
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- 3CCT switch installs in the junction box
- ACLED driverless technology
- 5 year warranty

#### SPECIFICATIONS

|               |  |
|---------------|--|
| Color Temp:   | 4000K,3500K,3000K                          |
| Input:        | 120 VAC,50/60Hz                            |
| CRI:          | 90   |
| Dimming:      | ELV: 100-10%                               |
| Rated Life:   | 54000 Hours                                |
| Mounting:     | Can be mounted on wall in all orientations |
| Standards:    | ETL, cETL,IP65<br>Wet Location Listed      |
| Construction: | Extruded aluminum body with PC diffuser    |




#### FINISHES:



Black

#### LINE DRAWING:



WS-W13348

# WAC LIGHTING

## Revels

### Outdoor Wall Sconce

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

| Model & Size  | Color Temp | Finish   | LED Watts | LED Lumens | Delivered Lumens |
|---------------|------------|----------|-----------|------------|------------------|
| WS-W13360 60" | 3000K      | BK Black | 28W       | 665        | 428              |
|               | 3500K      |          | 28W       | 665        | 428              |
|               | 4000K      |          | 28W       | 665        | 428              |

Example: **WS-W13360-40-BK**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

#### DESCRIPTION

Balanced with geometric precision. A slim bar of light glowing between the lines of a minimal profile.

#### FEATURES

- Illumination on both sides with acrylic diffuser
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- 3CCT switch installs in the junction box
- ACLED driverless technology
- 5 year warranty

#### SPECIFICATIONS

|               |  |
|---------------|--|
| Color Temp:   | 4000K,3500K,3000K                          |
| Input:        | 120 VAC,50/60Hz                            |
| CRI:          | 90   |
| Dimming:      | ELV: 100-10%                               |
| Rated Life:   | 54000 Hours                                |
| Mounting:     | Can be mounted on wall in all orientations |
| Standards:    | ETL, cETL,IP65<br>Wet Location Listed      |
| Construction: | Extruded aluminum body with PC diffuser    |




#### FINISHES:



Black

#### LINE DRAWING:



WS-W13360

# WAC LIGHTING

## Revels

### Outdoor Wall Sconce

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

| Model & Size  | Color Temp | Finish   | LED Watts | LED Lumens | Delivered Lumens |
|---------------|------------|----------|-----------|------------|------------------|
| WS-W13372 72" | 3000K      | BK Black | 28W       | 850        | 547              |
|               | 3500K      |          | 28W       | 850        | 547              |
|               | 4000K      |          | 28W       | 850        | 547              |

Example: **WS-W13372-40-BK**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

#### DESCRIPTION

Balanced with geometric precision. A slim bar of light glowing between the lines of a minimal profile.

#### FEATURES

- Illumination on both sides with acrylic diffuser
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- 3CCT switch installs in the junction box
- ACLED driverless technology
- 5 year warranty

#### SPECIFICATIONS

|                      |  |
|----------------------|--|
| <b>Color Temp:</b>   | 4000K,3500K,3000K                          |
| <b>Input:</b>        | 120 VAC,50/60Hz                            |
| <b>CRI:</b>          | 90   |
| <b>Dimming:</b>      | ELV: 100-10%                               |
| <b>Rated Life:</b>   | 54000 Hours                                |
| <b>Mounting:</b>     | Can be mounted on wall in all orientations |
| <b>Standards:</b>    | ETL, cETL,IP65<br>Wet Location Listed      |
| <b>Construction:</b> | Extruded aluminum body with PC diffuser    |




#### FINISHES:



Black

#### LINE DRAWING:



WS-W13372