

Product Family: Veneto

Sku Tested: S2234

Related Models N/A

Test Voltage: 120-277V

Control Type: ELV, TRIAC, MLV, 0-10V

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

| Manufacturer | Product | Model Number | Test Voltage (V) | Measured Dimming Range | Comments |
|--------------------------------------|----------------------|---------------|------------------|------------------------|---|
| | | | | Low End | |
| Adaptive Phase Dimmers | | | | | |
| Control4 | Adaptive | C4-APD120 | 120 | 0.2% | |
| Legrand | Adorne Touch (ELV) | ADTH700RMTUM1 | 120 | 3.0% | |
| Legrand | Adorne Touch (TRIAC) | ADTH700RMTUM1 | 120 | 1.0% | Not Recommended |
| Legrand | Radiant | RH703PTUW | 120 | 2.0% | |
| Legrand | Adorne (ELV) | ADTP703TUW4 | 120 | 5.0% | |
| Legrand | Adorne (TRIAC) | ADTP703TUW4 | 120 | 4.0% | Not Recommended |
| Cooper | AL Series | AAL06 | 120 | 1.0% | |
| Control4 | Adaptive | C4-APD277 | 277 | 98.0% | Flashing at high dimming level |
| Reverse Phase Dimmers (ELV) | | | | | |
| Lutron | Nova T | NTELV-600 | 120 | 3.0% | |
| Lutron | Diva | DVELV-300P | 120 | 2.0% | |
| Lutron | Maestro | MAELV-600 | 120 | 1.0% | |
| Lutron | Skylark | SELV-300P | 120 | 2.0% | |
| Leviton | Illumatech | IPE04-1LZ | 120 | 2.0% | |
| Lutron | Maestro | RRD-6NA | 120 | 1.0% | |
| Leviton | SureSlide | 6615-P0W | 120 | 10.0% | |
| Leviton | Decora | DSE06-10Z | 120 | 2.0% | |
| Lutron | Caseta | PD-5NE | 120 | 2.0% | |
| Lutron | Homeworks | HRD-5NE | 120 | 2.0% | |
| Lutron | Homeworks | HQRD-6NA | 120 | 1.0% | |
| Leviton | Renoir II | AWSMT-EBW | 120 | 0.8% | Flashing at low dimming level |
| Lutron | Grafik-Eye | GRX-3103-A-G | 120 | 1.0% | |
| Leviton | Renoir II | AWSMT-EBW | 277 | 100.0% | Flashing at low dimming level |
| Lutron | Grafik-Eye | GRX-3103-A-G | 277 | 100.0% | |
| Forward Phase Dimmers (TRIAC) | | | | | |
| Lutron | Maestro | MACL-153M-WH | 120 | 2.0% | |
| Lutron | Diva | DVCL-153P | 120 | 2.0% | |
| Legrand | Adorne Paddle | ADPD453LW2 | 120 | 64.0% | Flashing at high dimming level; Noise at 1 meter away |
| Lutron | Ariadni | AYCL-153PH | 120 | 1.0% | Flashing at low dimming level |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Schonbek's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Schonbek, and therefore Schonbek cannot ensure future compatibility. For any questions on this report, please contact Schonbek Customer Service at +1 800 836 1892 or lighting.na@schonbek.com

| Forward Phase Dimmers (TRIAC) Cont. | | | | | |
|-------------------------------------|-----------|-------------|-----|-------|--------------------------------|
| Lutron | Skylark | SCL-153P-WH | 120 | 1.0% | |
| Lutron | Maestro | MA-600-WH | 120 | N/A | Dimmer not responsive |
| Leviton | SureSlide | 6674-POW | 120 | 1.0% | |
| Lutron | Caseta | PD-6WCL | 120 | 1.0% | |
| Legrand | Harmony | HCL453PW | 120 | N/A | Flashing at all dimming levels |
| Legrand | Radiant | RHCL453PW | 120 | N/A | Flashing at all dimming levels |
| 0-10V Dimmers | | | | | |
| Lutron | Nova T | NTSTV | 120 | 5.0% | |
| Leviton | Decora | IP710-LFZ | 120 | 2.0% | |
| Control4 | Adaptive | C4-TV120277 | 120 | 2.0% | |
| Lutron | Diva | DVSTV | 120 | 2.0% | |
| Leviton | Renoir | AWSMT-7DW | 120 | 11.0% | |
| Legrand | Radiant | RH4FBL3PW | 120 | 2.0% | |
| Lutron | Nova T | NTSTV | 277 | 9.0% | |
| Leviton | Decora | IP710-LFZ | 277 | 2.0% | Flashing at low dimming level |
| Control4 | Adaptive | C4-TV120277 | 277 | 2.0% | Flashing at low dimming level |
| Lutron | Diva | DVSTV | 277 | 2.0% | Flashing at low dimming level |
| Leviton | Renoir | AWSMT-7DW | 120 | 11.0% | |
| Legrand | Radiant | RH4FBL3PW | 277 | 1.0% | Flashing at low dimming level |

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Schonbek's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Schonbek, and therefore Schonbek cannot ensure future compatibility. For any questions on this report, please contact Schonbek Customer Service at +1 800 836 1892 or lighting.na@schonbek.com