

**Product Family:** Verve LED

**Sku Tested:** S2613

**Related Models** N/A

**Test Voltage:** 120 OR 277V

**Control Type:** ELV, TRIAC, MLV

**Test Notes:** Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
<b>Adaptive Phase Dimmers</b>					
Control4	Adaptive	C4-APD120	120	0.2%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	96.0%	Flashing at high dimming level
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	N/A	Not Recommended
Legrand	Radiant	RH703PTUW	120	17.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	15.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	17.0%	Not Recommended
Cooper	AL Series	AAL06	120	54.0%	Flicker at high dimming level
Control4	Adaptive	C4-APD277	277	1.0%	
<b>Reverse Phase Dimmers (ELV)</b>					
Lutron	Nova T	NTELV-600	120	10.0%	
Lutron	Diva	DVELV-300P	120	6.0%	
Lutron	Maestro	MAELV-600	120	2.0%	
Lutron	Skylark	SELV-300P	120	6.0%	
Leviton	Illumatech	IPE04-1LZ	120	8.0%	
Lutron	Maestro	RRD-6NA	120	2.0%	
Leviton	SureSlide	6615-P0W	120	20.0%	
Leviton	Decora	DSE06-10Z	120	4.0%	
Lutron	Caseta	PD-5NE	120	7.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at all dimming levels
Lutron	Homeworks	HQRD-6NA	120	2.0%	
Leviton	Renoir II	AWSMT-EBW	120	1.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	1.0%	
Leviton	Renoir II	AWSMT-EBW	277	2.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	277	14.0%	
<b>Forward Phase Dimmers (TRIAC)</b>					
Lutron	Maestro	MACL-153M-WH	120	3.0%	
Lutron	Diva	DVCL-153P	120	0.9%	
Legrand	Adorne Paddle	ADPD453LW2	120	17.0%	
Lutron	Ariadni	AYCL-153PH	120	2.0%	

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Schonbek's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Schonbek, and therefore Schonbek cannot ensure future compatibility. For any questions on this report, please contact Schonbek Customer Service at +1 800 836 1892 or [lighting.na@schonbek.com](mailto:lighting.na@schonbek.com)

Forward Phase Dimmers (TRIAC) Cont.					
Lutron	Skylark	SCL-153P-WH	120	41.0%	Flashing at low dimming level
Lutron	Maestro	MA-600-WH	120	32.0%	Flashing at low dimming level
Leviton	SureSlide	6674-POW	120	16.0%	Flicker below 16%
Lutron	Caseta	PD-6WCL	120	24.0%	Flicker below 24%
Legrand	Harmony	HCL453PW	120	18.0%	Flicker below 18%
Legrand	Radiant	RHCL453PW	120	58.0%	Flicker at high dimming level

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Schonbek's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Schonbek, and therefore Schonbek cannot ensure future compatibility. For any questions on this report, please contact Schonbek Customer Service at +1 800 836 1892 or [lighting.na@schonbek.com](mailto:lighting.na@schonbek.com)