

Date _____

Name _____

Client _____

Project name _____

Quote# _____

Type/Quantity _____

Listings





25/04/2022 14:52:11

Specification Sheet

LOGIC R1 93511 6 213 471 811 951

[Weblink](#)



Cutout shape/size:	⊘ 3" 11/16
Recessed depth:	4" 15/16
Available colors:	ALU ANODIZED (6 213 471 811 951 ANO)
INCL.CABLE 2 x 20 AWG 5' LED 7,1W / CRI>90 / 3500K / 837lm REFLECTOR SP-11° EXCL.LED POWER SUPPLY 24V-DC (non-dimmable) For other CRI or KELVIN, contact factory	
LED Technics:	Light source: 837 lm // 7 W // 118 lm/W Luminaire: 788 lm // 8 W // 97 lm/W
24V-DC	
Class 2	Yes
Ada	N.a.
Weight:	2.2 LBS
Protection level:	IP67 - suitable for wet locations
Minimum distance:	n.a.
Options:	JUNCTION BOX IP68 CONNECTOR 3P

Requirements :
 GENIE BOX 90 R
 LED POWER SUPPLY 24V-DC (Remote)

For detailed installation instructions, please consult the manual. [6_213_471_811_XXX_HAND.pdf](#)

LOGIC R1 93511
6 213 471 811 951

Related references

LED POWER SUPPLIES - REMOTE

[Weblink / Specsheet](#)

LED POWER SUPPLY 24V-DC / 90W
DIM1
6 300 89 24 90 ED1
120-277V / 60Hz
Number of luminaires: 10

[Weblink / Specsheet](#)

LED POWER SUPPLY 24V-DC / 96W
DIM8
6 300 89 24 96 ED8
120V / 60Hz
Number of luminaires: 11

Related references

GROUND MOUNTING BOXES

[Weblink / Specsheet](#)

GENIE BOX 90 R
6 213 19 09

Related references

WATERPROOF CONNECTION PARTS

[Weblink / Specsheet](#)

IP68 CONNECTOR 3P
6 216 12 02

[Weblink / Specsheet](#)

IP68 CONNECTOR 5P
6 216 12 03

[Weblink / Specsheet](#)

JUNCTION BOX
6 216 12 00

Related project picture of product family:

