TECH LIGHTING

PRODUCT FEATURES

- Solid faceted crystal manufactured in Czech Republic. Custom engineered natural brass connectors
- This item is made of natural brass. It is a living finish that will patina and warm with age which adds richness. If it gets an uneven patina or spots, a brass cleaner can restore the finish
- Remote and surface mount driver options available. An optional mud-in canopy kit can be ordered separately in conjunction with the 'Remote' driver option for the most minimal ceiling appearance.
- · Contact factory for custom configurations
- For minimal ceiling appearance, order the optional mud-in canopy kit in conjunction with the 'Remote' driver. It can be viewed here
- Protected by a 5-year warranty. Please visit the "About Us" Page on techlighting.com for more for warranty details. Patent Pending



Natural Brass

LAMPING

Includes 36.9 watt, 2034 total delivered lumens, 90 CRI 2700K or 3000K LED modules. Remote dimmable with most LED compatible ELV and TRIAC dimmers. 277V dimmable with 0-10V dimmers. Surface dimmable with ELV and TRIAC dimmers. Remote 120V or 277V. Surface 120V-277V. Can be installed on a sloped ceiling up to 45°.



ORDFRING INFORMATION

700CLR	SHAPE OR SIZE	FINISH	LAMP	
	108 108	NB NATURAL BRASS	-LED927R	INTEGRATED LED 90 CRI 2700K 120V (REMOTE)
		N POLISHED NICKEL	-LED927R-27	77 INTEGRATED LED 90 CRI 2700K 277V (REMOTE)
			-LED927S	INTEGRATED LED 90 CRI 2700K 120V-277V UNIVERSAL (SURFACE)
			-LED930R	INTEGRATED LED 90 CRI 3000K 120V (REMOTE)
			-LED930R-27	77 INTEGRATED LED 90 CRI 3000K 277V (REMOTE)
			-LED930S	INTEGRATED LED 90 CRI 3000K 120V-277V UNIVERSAL (SURFACE)

700CLR	
JOB NAME	
NOTES	




COLLIER 108 CHANDELIER

TECH LIGHTING

SPECIFICATIONS

PRIMARY MATERIAL	Crystal			
SHADE MATERIAL	Crystal			
NET WEIGHT	20 lbs			
HEIGHT	118.4in			
WIDTH	2in			
LENGTH	2in			
UP LIGHT / DOWN LIGHT / BOTH?				
WET LISTED				
DAMP LISTED	Yes			
DRY LISTED				
MIN. HANGING HEIGHT	118.4in			
MAX HANGING HEIGHT	118.4in			
TOTAL CORD LENGTH				
TOTAL STEM LENGTH				
STEM QTY				
SLOPED CEILING ADAPTABLE?	Yes 45° Max			
GENERAL LISTING	ETL Listed			
INCLUDES				



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		2064		
WATTS		36.9		
MAX WATTAGE PER BULB		36.9W		
		120V ELV, TRIAC		
INPUT VOLTAGE/ DIMMING TYPE		277V 0-10V		
		Universal 120V-277V ELV, TRIAC		
CCT		2700K		
ССТ		3000K		
CRI		90 CRI		
LED LIFETIME				
L70		>50000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

 $^{* \} Dimming information available at \underline{www.techlighting.com/Downloads\#dimming}$

T20/T24/JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

 $^{^*}$ If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



^{**}Visit techlighting.com for specific warranty limitations and details.