Alphabet Of Light Circular 90 suspension

SPECIFICATIONS

1206008A





Design By = BJARKE INGELS GROUP

Collection Architectural

Colors & Finishes

White (Diffuser & Canopy)

Grey (Body)

Materials

- Illuminated tubes in opaque injection molded PMMA resin
- 6 modules assembled
- 360° light emission
- Aluminum frame suspended by steel cables

Specifications	
Delivered lumens	6040lm
Light output ratio	109.83lm/W
Power consumption	55W
Led type	48.8W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire / Dimmable 0-10V**
Input Voltage	120-277V
Driver	EFORE - 1 x RCL050-1400A


**2-wire only dimmable at 120V

Features & Accessories

• Suitable for damp locations

• Driver is compatible to both 2-wire dimming and 0-10V dimming options

Dimensions




Light distribution

Direct/Indirect

Luminaire weight 13.23 lbs / 6 kg

Warranty





Packaging

1 Box

1 x 43-13/16" x 44-9/16" x 8-3/4" / 21.16 lbs - 111 cm x 113 cm x 22 cm / 9.6 kg