Chlorophyll_Bulbo collection




Table Lamps | 100-240 V 3 x powerLED 7 W DC 1000 mA **8010**



Technical data	
Designer	Lorenzo Antonioni
Туре	Table Lamps
Installation position	Floor
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward
Power	7 W
Frequency	60 - 50 Hz
C.C. / C.V.	AC
Safety class	2
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	1200 m
Electric socket	Type C
Resin potting	No
Type of light emission	Single emission
Net weight	0.570 Kg
Electrostatic discharge protection	No
Surge protection	No





Finishing casing			
Colour	Terracotta		
Processing	Lacquering		

Finishing diffuser		
Material	Acrylic glass	
Colour	opaline	
Processing	Satin finishing	

Material Aluminium	Finishing mounting frame		
0 1 1 1 1 1 1 1			
Colour Anodised Aluminum			
Processing Anodisation			

Chlorophyll_Bulbo collection



Table Lamps | 100-240 V | 3 x powerLED 7 W DC 1000 mA **8010**

Single emission table lamps for indoor application. The -- LED light source with a general lighting light distribution is composed of 3 powerled LEDs.

The device body and features a terracotta finish, processed by means of lacquering; the diffuser is made of acrylic glass with a satin finishing treatment; the mounting frame is made of aluminium, with a anodised aluminum finish, processed by means of anodisation. The ingress protection degree is IP20; the total weight is of 0.570 kg.

The total absorbed power is 7 W. The power supply cable is included and features a 1200 m lenght.

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25
LED Life / Failure Ratio	
L80 B20 C25 80000h	