


# AVIATOR 54" Ceiling Fan

FR-W1811-54

## MODERN FORMS SMART FANS



### PRODUCT DESCRIPTION

Inspired by the golden age of flying, this smart fan takes technology to the next level. Pair it with the exclusive Modern Forms app to save on energy costs and intuitively create schedules that adapt to your behavior. Two simulated wood finishes contrast with the matte black or graphite housings for an understated look in interior or exterior spaces. Available option LED light kit sold separately.

### SPECIFICATIONS

**Construction:** Aluminum  
**Blade:** 13° Pitch, 60" sweep, ABS  
**Downrod:** 1" O.D. x 4.5"H included  
**Mounting Slope:** Up to 30°  
**Lead Wire:** 80"  
**Hanging Weight:** 13 lbs  
**Total Power:** 32W  
**Standards:** ETL/cETL Wet Location listed

### FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit sold separately
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Optional RF remote control with wall cradle sold separately
- Compatible with Modern Forms app

### WIRELESS PERFORMANCE

**RF Pairing Distance:** Up to 30 ft from fan  
**Wi-Fi Range:** Up to 150 ft\*

### ESTIMATED AIR PERFORMANCE

**Airflow:** 6800 cubic ft per minute on high  
**Power:** 32 watts on high  
**Airflow Efficiency:** 209 cubic ft per minute per watt  
**RPM:** 145 RPMS on high

### ORDER NUMBER

Model	Housing		Blade	
FR-W1811-54	<b>GH</b>	<i>Graphite</i>	<b>WG</b>	<i>Weathered Gray</i>
	<b>MB</b>	<i>Matte Black</i>	<b>DK</b>	<i>Distressed Koa</i>

### OPTIONAL LUMINAIRE (Sold Separately)

Model	Finish	
F-1811-LED	<b>GH</b>	<i>Graphite</i>
	<b>MB</b>	<i>Matte Black</i>

Example: FR-W1811-54-GH/WG

Example: F-1811-LED-GH

\*Results may vary based on application and surroundings.



modernforms.com  
 Phone (866) 810.6615  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122







Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91760

# AVIATOR 54" Ceiling Fan

FR-W1811-54L

## MODERN FORMS SMART FANS

### OPTIONAL ACCESSORIES

<b>RF Wall Control</b>		<b>F-WC</b>	<b>WT</b> White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.
<b>RF Remote Control</b>		<b>F-RC</b>	<b>WT</b> White	Sold separately. Control fan speed and light brightness, and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.
<b>Wi-Fi Touch Panel Wall Control</b>		<b>F-TS</b>	<b>BK</b> Black <b>WT</b> White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
<b>Downrod</b>		<b>XF-12</b> 12in <b>XF-18</b> 18in <b>XF-24</b> 24in <b>XF-36</b> 36in <b>XF-48</b> 48in <b>XF-60</b> 60in <b>XF-72</b> 72in	<b>AS</b> Automotive Silver <b>BA</b> Brushed Aluminum <b>BZ</b> Bronze <b>CFI</b> Carbon Fiber** <b>DW</b> Dark Walnut <b>GB</b> Gloss Black <b>GH</b> Graphite <b>GW</b> Gloss White <b>KO</b> Koa† <b>MB</b> Matte Black Matte <b>MW</b> White <b>OB</b> Oil Rubbed Bronze <b>SS</b> Stainless Steel <b>TT</b> Titanium Silver	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
<b>Downrod Couplers</b>		<b>XF-I</b>		Connects two downrods together.
<b>Sloped Ceiling Kit</b>		<b>XF-SCK</b>		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: RF Wall Control - **F-WC-WT**, RF Remote Control - **F-RC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW**

### SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

### SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope Pitch	1/12 pitch	2/12 pitch	3/12 pitch	4/12 pitch	5/12 pitch	6/12 pitch	7/12 pitch	8/12 pitch	9/12 pitch	10/12 pitch	11/12 pitch	12/12 pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

**NOTE:** Recommended maximum downrod length of 72" with 80" lead wire

\*\*Carbon Fiber downrods available in 12", 18", 24" and 36"

†Koa downrods available in 12", 18", 24" and 36"

modernforms.com  
Phone (866) 810.6615  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760