TOL0102



Design By =

Michele De Lucchi Giancarlo Fassina

Collection =

Design







Colors & Finishes =



Materials =

- Arms and diffuser in aluminum
- Joints and tension control knobs in polished die-cast aluminum
- Tension cables in stainless steel
- Floor support base in weighted steel with stamped aluminum cover
- · Stem in steel


Specifications =

Delivered lumens	357lm
Light output ratio	33.4lm/W
Power consumption	10.7W
Led type	10W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	DIMMABLE (On Head)
Input Voltage	120-240V
Driver	Plug-in

Features & Accessories =

- Fully adjustable, articulated arm structure
- Tiltable and rotatable diffuser (90 degrees in both directions)
- Interchangeable plug options accommodate most electrical outlets for global diversity

Dimensions =



Packaging =

3 Boxes


1 x 10-5/16" x 7-9/16" x 33-3/16" / 3.99 lbs - 26 cm x 19 cm x 84 cm / 1.809 kg

1 x 41-13/16" x 1-11/16" x 1-11/16" / 1.54 lbs - 106 cm x 4 cm x 4 cm / .7 kg

1 x 15-13/16" x 16-1/4" x 4-7/16" / 16.76 lbs - 40 cm x 41 cm x 11 cm / 7.6 kg

Light distribution

Direct



Luminaire weight =

17.54 lbs / 7.96 kg

Warranty = 5 year limited warranty

Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane