PHOTON 48 CHANDELIER

TECH LIGHTING

PRODUCT FEATURES

- Playful starburst design can be installed in multiples at varying heights for a dramatic art installation
- High performance, energy efficient integrated LED light source with 3,000K Color Temp and 90 CRI
- Fully dimmable with most ELV dimmers to create just the right atmosphere
- Solid acrylic arms with aluminum core construction for beauty and durability
- Protected by a 5-year warranty. please go to www.techlighting.com for warranty details
- 10 ft. of cord included to adjust installation height. canopy finish matches fixture finish



LAMPING

Includes 10' of field-cuttable cable. LED includes (18) 2 watt 2709 total delivered lumens 90 CRI 3000K LED modules. Dimmable with most LED compatible ELV and TRIAC dimmers. 277V compatible with 0-10V dimmers.





Satin Nickel

Aged Brass

ORDERING INFORMATION

| 700PHT48 | FINISH | LAMP |
|----------|----------------|--|
| | R AGED BRASS | -LED930 INTEGRATED LED 90 CRI 3000K 120V |
| | S SATIN NICKEL | -LED930-277 INTEGRATED LED 90 CRI 3000K 277V |
| | | |

| 700PHT48 | | | | | |
|----------|--|--|--|--|--|
| JOB NAME | | | | | |
| NOTES | | | | | |




PHOTON 48 CHANDELIER

TECH LIGHTING

SPECIFICATIONS

| HARDWARE MATERIAL | Metal | | | |
|-------------------------------|----------|--|--|--|
| SHADE MATERIAL | Acrylic | | | |
| NET WEIGHT | 18.5 lbs | | | |
| HEIGHT | 31.8in | | | |
| WIDTH | 48in | | | |
| LENGTH | 48in | | | |
| UP LIGHT / DOWN LIGHT / BOTH? | | | | |
| WET LISTED | | | | |
| DAMP LISTED | Yes | | | |
| DRY LISTED | | | | |
| MIN. HANGING HEIGHT | 58.2in | | | |
| MAX HANGING HEIGHT | 144.2in | | | |
| TOTAL CORD LENGTH | 120in | | | |
| TOTAL STEM LENGTH | | | | |
| STEM QTY | | | | |
| SLOPED CEILING ADAPTABLE? | | | | |
| GENERAL LISTING | | | | |
| INCLUDES | | | | |



LAMPING SPECIFICATIONS

| | LEDIAMD | INTEGRATERIER | NONLED | NOLAMB |
|-----------------------|----------|----------------|---------|---------|
| | LED LAMP | INTEGRATED LED | NON LED | NO LAMP |
| DELIVERED LUMENS | | 2709 | | |
| WATTS | | 2 | | |
| MAX WATTAGE PER BULB | | 35.1W | | |
| INPUT VOLTAGE | | 120V | | |
| INPUT VOLTAGE | | 277V | | |
| DIMMING TYPE* | | ELV, TRIAC | | |
| DIMINING ITPE | | 0-10V | | |
| ССТ | | 3000K | | |
| CRI | | 90 CRI | | |
| LED LIFETIME | | | | |
| L70 | | | | |
| AVERAGE BULB HOURS | | 50000 | | |
| FIELD SERVICEABLE LED | | | | |
| LAMP BASE | | Integrated LED | | |
| LAMP SHAPE | | Integrated LED | | |
| LAMP INCLUDED? | | Υ | | |
| WARRANTY** | | 5 Years | | |

^{*} Dimming information available at www.techlighting.com/Downloads#dimming ** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 INFORMATION

| | Integrated LED | Replacement LED Lamp | No Lamp * |
|--|-------------------|-------------------------|--------------|
| This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6. | No | | |
| This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to anc sold in California. | N/A | | |

^{*}If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

