


Hologram 3D



Pendant Luminaires | 220-240 V
topLED 3 W DC - 3 W AC | CRI 80
8997



Technical data	
Designer	Linea Light
Construction year	2020
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	Spot
Light emission direction	downward
Power	3 W
CCT / Tone	3000 K
Source lumens	200 lm
Frequency	50 - 60 Hz
CCT / Tone	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Resin potting	No
Type of light emission	Single emission
Net weight	0.42 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing	
Material	Aluminium
Colour	embossed white RAL 9003
Processing	Coating

Finishing diffuser	
Material	PMMA
Colour	transparent

Finishing mounting frame	
Material	Iron
Colour	embossed white RAL 9003
Processing	Coating

Cables Pendant Luminaires	
Max cable length	2600 mm



Pendant Luminaires | 220-240 V | topLED 3 W DC - 3 W AC | CRI 80 | Color temperature : 3000 K
8997

Single emission pendant luminaires for indoor application. The warm white LED light source with a spot light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 200 lm, with a 66.7 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of pmma; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 0.42 kg.

The total absorbed power is 3 W. The power supply cable is included and features.


The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Light Output Ratio (LOR)	41 %
Source lumens	200 lm
Delivered lumens	82.43 lm
Consumption	3 W
Luminaire efficacy	27 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25
LED Life / Failure Ratio	
L70 B20 C0 72.5h	

UGR	
UGR axial	< 16
UGR transversal	< 16
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Light distribution simmetry	Symmetrical
C0/C180 optics	20°



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	0.17 0.18	E(0°) 1846 E(C90) 892 E(C0) 882
1.0	0.35 0.36	E(0°) 461 E(C90) 223 E(C0) 221
1.5	0.52 0.55	E(0°) 205 E(C90) 99 E(C0) 98
2.0	0.70 0.73	E(0°) 115 E(C90) 56 E(C0) 55
2.5	0.87 0.91	E(0°) 74 E(C90) 36 E(C0) 35
3.0	1.05 1.09	E(0°) 51 E(C90) 25 E(C0) 25

— C0/C180 (Half-peak divergence: 20.6°)
 — C90/C270 (Half-peak divergence: 19.8°)