



LD304 Birthing Bed

Intermediate siderail position moves siderails back and allows mom better visibility and closeness to the bassinet and baby

Length-adjustable footrests and calf supports offers nearly infinite positioning for customized comfort and slides into place with an easy-squeeze handle

Moves mom closer to the perineal edge, reducing strain on you while providing proper back support for mom

Removable Lock-Rite® foot section Simple, safe and exceptionally easy to handle, the Lock-Rite design provides visual confirmation that it is securely locked into place

- Lock-Rite slide-off foot section
- Lightweight, self-standing foot section
- Glideaway foot supports with six-way adjustability
- Single-button Trend.
- Three-position siderails
- In-rail motion controls with lockout
- 17.5-inch (44 cm) low bed height
- 5-inch (13 cm) Ultra Comfort head and seat support surface
- 3-inch (8 cm) foot mattress
- 6-inch (15 cm) Omni Surface casters with wheel covers
- Locking-caster steering
- Four-wheel, steel-ring brake system with centrally located activation pedal
- 33-inch (84 cm) mattress width with four motor functions (head, bed, foot, Trend.)
- Automatic pelvic tilt
- CPR release



Mattress Options Sold Separately

With over 25 years of experience, iMedical offers industry-leading refurbished hospital beds & stretchers. We meet FDA and ISO 9001:2015 requirements. Our process includes complete disassembly, rework or replacement of all worn parts. Each unit is then rebuilt to meet OEM standards. Each unit is tested, inspected and warranted. We offer white glove delivery and installation.

LD304 Birthing Bed

Specifications

Model number	4701
Overall length	93" (236 cm)
Overall width	
Siderails up	41" (104 cm)
Siderails down	37" (94 cm)
Lift capacity	
Bed	500 lb. (226.7 kg)
Foot section	300 lb. (136.0 kg)
Height range (to litter top)	
High	35.5" (90 cm)
Low	17.5" (44 cm)
Litter positioning	
Backrest	0°-70°
Pelvic tilt	4°
Maximum Trend.	8°
Patient surface	33" x 81" (84 x 206 cm)
Support surface thickness	
Head/seat	5" (13 cm)
Foot	3" (8 cm)
Seat depth	
Standard	12.5" (32 cm)
With Skoocher	12.5-8.5" (32-22 cm)
Caster diameter	
Standard	6" (15 cm)

Electronics

Agency approvals	C-US UL (120 V AC)
Volts	120 VAC (Domestic) 230 VAC (International)
Ampere rating	10 A
Current leakage	< 300 microamperes
Frequency	60 Hz (Domestic) 50/60 Hz (International)
Hospital grade plug	Yes
EMC Compatible	Yes
Motor function	Bed, head, foot, Skoocher (optional), Trend.



With over 25 years of experience, iMedical offers industry-leading refurbished hospital beds & stretchers. We meet FDA and ISO 9001:2015 requirements. Our process includes complete disassembly, rework or replacement of all worn parts. Each unit is then rebuilt to meet OEM standards. Each unit is tested, inspected and warrantied. We offer white glove delivery and installation.