

# estelan

## Cat6A U/UTP Cable

### Special Filler




#### Application:

- Horizontal Cabling, Backbone Cabling, Digital and Analog Audio and Video Signal Transfer
- IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T, 10Gbase-T
- IEEE 802.5 16 MB; ISDN; TPDDI; ATM
- Power over Ethernet (PoE / PoE+) / Type 1-4
- Enhanced Alien Cross Talk Performance
- Patented Design

#### Standards:

- ANSI / TIA-568.2-D & ISO / IEC 11801
- EN 50173-1; EN 50288-10-1
- IEC 61156-5
- IEEE 802.3 af / at / bt



- Outer Sheath
- Rip Cord
- Special Filler
- Copper Conductor Color Insulation

#### Flame Resistance:

LSZH: EN 60332-1; EN 60754-1 & 2, EN 61034-2, Class CPR-Eca

#### Construction:

Conductor	ETP-grade copper Ø 23 AWG
Insulation	Polyolefin
Twisting	2 insulated conductors forming one pair
Cable Lay-up	4 twisted pairs / innovative design filler
Sheath	LSZH
Nominal Cable Diameter	7.6 mm

#### Mechanical Properties:

Bending Radius : 4 x Cable Diameter at  $-20^{\circ}\text{C} \pm 1^{\circ}\text{C}$   
 Pulling Force : 112 N

#### Temperature Range

Installation :  $0^{\circ}$  to  $+50^{\circ}\text{C}$   
 Operation :  $-20^{\circ}$  to  $+75^{\circ}\text{C}$

### Electrical Properties at 20°C:

Conductor Resistance	: < 9.38 Ω / 100m	Capacitance Unbalance	: 330pF / 100m
Mutual Capacitance	: < 5.6nF / 100m	Delay Skew	: < 45nS
Resistance Unbalance	: 5% Max	Propagation (NVP)	: 65%



### Transmission Characteristics at 20°C:

Frequency (MHz)	Insertion Loss (dB) Max.	RL (dB) Min.	NEXT (dB) Min.	PSNEXT (dB) Min.	ACRF (dB) Min.	PSACRF (dB) Min.	Prop.Delay (ns) Max.
1	2.1	20.0	74.3	72.3	67.8	64.8	570
4	3.8	23.0	65.3	63.3	55.8	52.8	552
10	5.9	25.0	59.3	57.3	47.8	44.8	547
16	7.5	25.0	56.2	54.2	43.7	40.7	545
20	8.4	25.0	54.8	52.8	41.8	38.8	543
31.25	10.5	23.6	51.9	49.9	37.9	34.9	542
62.5	15.0	21.5	47.4	45.4	31.9	28.9	541
100	19.1	20.1	44.3	42.3	27.8	24.8	540
200	27.6	18.0	39.8	37.8	21.8	18.8	539
250	31.1	17.3	38.3	36.3	19.8	16.8	538
300	34.3	16.8	38.1	35.1	18.3	15.3	537
500	45.3	15.2	33.8	31.8	13.8	10.8	536

#### Color Code:

PAIR NO	COLOR
1	White-Blue Stripe and Blue
2	White-Orange Stripe and Orange
3	White- Green Stripe and Green
4	White-Brown Stripe and Brown

#### Jacket Color (C1 C2):

 Grey <b>(01)</b>	 Blue <b>(02)</b>
 Red <b>(03)</b>	 White <b>(04)</b>
 Violet <b>(05)</b>	 Orange <b>(06)</b>
 Yellow <b>(07)</b>	

**Packaging:** Available in Reel of 305m(1000ft) **(04)** / Reel of 500 m(1640ft) **(05)**  
**(P1 P2)** Length Tolerance: +/- 2 meter

### Product Code / Part No:

Part No	Product Name	Euro Class	ETL Verified	UL Listed	UL Verified
32127-C1C2P1P2	Cat 6A U/UTP-LSZH	CPR-Eca	✓	✓	on demand

Note: Higher CPR Category will be made available on demand

01/042023



The information given herein, including drawings, illustrations and schematics are intended for illustration purposes only and is believed to be reliable. However, Sterlite Technologies makes no warranties to its accuracy or completeness and disclaims any liability in connection with its use. Sterlite Technologies obligations shall be only set forth in Sterlite Technologies standard terms and conditions of the sale and in no case, Sterlite Technologies be liable for any incidental, indirect or consequential damages arising out of sale, resale, use or misuse of the product.

Users of Sterlite Technologies products should make their own evaluation to determine the suitability of such each product for the specific application.