

Roman House Lysons Avenue Ash Vale, GU12 5QF Tel: +44 (1252) 451600

email: miguard@responseelectronics.com



miGuard MIO2

Wirefree Magnetic Door/Window Contact Detector (Two-Way)

Summary:

The M102 is a Door/Window Contact (Two-Way) that can be installed on doors, windows and any other objects that open and close. The sensor transmits signals to the control panel when a magnet mounted near the sensor is moved away. It will also transmit an alert signal to the control panel in case of a low battery. External input for a wired accessory is available at the N/C interface. The tamper protection ensures that sabotage attempts to move the contact will result in alarm activation. Using the sensor on an Entry/Exit route provides protection when the main Entry points are opened.



- Compatible with any miGuard alarm system (A8, A9, A11, G3, G5)
- Door/Window or any objects that open & close
- LED Indicator for Intruder Detection and low battery
- Transmit distance < 80m (in open area)

Kit Includes:

Transmitter detector x 1
Magnet x 1
AA 1.5V LR6 Battery x 1
Fixing packs



Key Features:

- Door/Window protection
- Low battery transmitter to the control panel
- Ideal for Entry/Exit routes
- Pet Tolerant detector
- Tamper Protection
- Battery powered
- Energy Saving

Specification:

Product Name:	Magnetic Contact Detector
Model No.:	M102
Power Supply:	DC 1.5V (AA 1.5V LR6 Battery x 1pc)
Standby Current:	≤ 35uA (Powered by Batteries)
Alarm Current:	≤ 10mA
Transmitting Distance:	≤ 80m (in open area)
Radio Frequency:	433MHz
Housing Material:	ABS Plastic
Operation Condition:	Temperature: -10 °C ~ 55 °C
	Humidity: ≤ 80% (non-condensing)
Size (L x W x H):	Transmitter: 70mm x 34mm x 19mm
	Magnet: 51mm x 13mm x 14mm
EAN:	5060215563023
Outer Carton Qty:	200
Outer Carton Dimensions:	355 x 295 x 240mm
Outer Carton Weight:	14Kgs