

LED 电源规格书 LED Power Supply Specification

CURTOMER / 客户:	
PRODUCT / 产品类型:	LED Power Supply/LED驱动电源
MODEL NO. / 产品型号:	WP-HHA-075U Series
PART NO./物料编号:	

DESIGNED BY / 拟制	CHECKED BY / 审核	APPROVED BY / 批准
Date / 日期:	Date / 日期:	Date / 日期:

CUSTOMER APPROVED SIGNATURES 客户承认签核		
Testing Engineer / 测试工程师	CHECKED BY / 审核	APPROVED BY / 批准
Date / 日期:	Date / 日期:	Date / 日期:
For confirmation, please sign and return this specification to us. 客户确认签字, 盖章后请回传一份承认书给我司.		

1. Electrical / 电气特性

1.1 Input characteristics / 输入特性

Classification / 类别	Subject of entry / 项目	
Input characteristics 输入特性	Rated input voltage / 额定输入电压	120-277Vac
	Range input voltage / 电源输入电压范围	108-305Vac
	Input current / 输入电流	<0.8A
	Input frequency / 输入频率	50/60Hz
	Input frequency range / 输入频率范围	47-63Hz
	Turn on delay time / 启动时间	≤500ms
	No-load power consumption / 空载功耗	≤2W
	Standby power consumption / 待机功耗	<0.8W
	Inrush current / 浪涌电流	<65A
	Power factor (@70%Load to Full load) / 功率因数	≥0.9
	THD (@70%Load to Full load) / 总谐波失真	≤20%

1.2 Output Characteristics / 输出特性

Constant Current Mode / 定电流模式 (CV测试)

Model No. / 型号	Output Voltage range / 输出电压范围 (V)	Rated Current 额定电流 (mA)	OVP / 过压保护 (V)	Output power (Rated) / 输出功率 (额定) (W)	Efficiency / 效率 (%) (Full load)		Output ripple (peak to peak) 输出纹波 (峰-峰值) ①
					@120Vac	@277Vac	
WP-HHA-075U0521100	30-52	1100	63	57.2	≥90	≥90	<5V
WP-HHA-075U0521150	30-52	1150	63	59.8	≥90	≥90	<5V
WP-HHA-075U0521200	30-52	1200	63	62.4	≥90	≥90	<5V
WP-HHA-075U0521250	30-52	1250	63	65	≥90	≥90	<5V
WP-HHA-075U0521300	30-52	1300	63	67.6	≥90	≥90	<5V
WP-HHA-075U0521350	30-52	1350	63	70.2	≥90	≥90	<5V
WP-HHA-075U0521400	30-52	1400	63	72.8	≥90	≥90	<5V
WP-HHA-075U0521450	30-52	1450	63	75.4	≥90	≥90	<5V
WP-HHA-075U0521500	30-52	1500	63	78	≥90	≥90	<5V
WP-HHA-075U0481550	30-48	1550	63	74.4	≥90	≥90	<5V
WP-HHA-075U0461600	30-46	1600	63	73.6	≥90	≥90	<5V
WP-HHA-075U0441700	24-44	1700	50	74.8	≥88	≥89	<5V
WP-HHA-075U0421800	24-42	1800	50	75.6	≥88	≥89	<5V
WP-HHA-075U0381900	24-38	1900	50	72.2	≥88	≥89	<5V
WP-HHA-075U0382000	24-38	2000	50	76	≥88	≥89	<5V

Note / 注释①

Ripple noise measurement method / 纹波噪声测量方法

10% of nominal output voltage (whichever is greater), measured at 20MHz bandwidth with 0.1uF ceramic capacitor in parallel with 10uF electrolytic capacitor connected at the end of the output connector.

额定输出电压的 10%，测试条件：输出端由 0.1uF 瓷片电容和 10uF 电解电容并联，20M 带宽范围测试。

1.3 protection Characteristics / 保护特性

1.3.1 Short circuit protection / 短路保护

Hiccup/short happened between the output terminals and shall not result in fire and any damage. The power no output, output will auto recover upon removal of over load.


当输出端短路时，产品输入功率降低或无输出且不会损伤，当短路情况解除后，产品将会自动恢复正常。

1.3.2 Other protection / 其他保护

Rely on input fusing.


电流保险丝。

1.3.3 Inrush current Waveform/浪涌电流波形




1.3.4 Derating curve/冗余曲线图

	-40° C	-25° C	0° C	25° C	45° C	60° C
120V	100%	100%	100%	100%	100%	100%
277V	100%	100%	100%	100%	100%	100%




1.3.5 Static characteristics/静态特征


108Vac	120V	220V	240V	277V	305V
100%	100%	100%	100%	100%	100%




1.3.6 Efficiency VS Load Curve/效率-负载曲线



1.3.7 Power Factor vs. Load Curve/功率因素-负载曲线



1.3.8 THDI vs. Load Curve/总谐波失真-负载曲线



1.4 Environmental/环境系数

Classification/类别	Subject of entry/项目	
Safety&EMC 安规和电磁兼容	Safety Standards / 安规标准	UL8750/CAN/CSA-C22.2 NO. 250.13
	EMC / 电磁兼容	EN55015 and FCC part 15 class B.
Hi-Pot / 耐压	I/P-O/P/输入-输出	1.6KVac,5mA,60S;
	I/P-FG/输入-地	1.5KVac,5mA,60S;
	O/P-FG/输出-地	1.5KVac,5mA,60S;
lightning surge 雷击浪涌	ICE61000-4-5	L-N :2KV L&N-PE:4KV
Insulation Resistance 绝缘阻抗	I/P-O/P; O/P-FG; I/P-FG	100Mohm/500Vdc
Leakage current 漏电流	277Vac input / 277V交流输入漏电流	<0.7mA
Environmental 环境系数	MTBF / 平均间隔故障时间	200,000 hours at 25°C ambient temperature
	Operation temperature / 工作温度	-40 °C to 60 °C
	Humidity / 湿度	5% to 95%
	Storage temperature / 储存温度	-40°C to 85°C
	Protection Class/防护等级	IP65
	Environment rating/环保标准	RoHS
	Case Size/外壳尺寸(L*W*H)mm	L*W*H: 175*49.7*30mm

2. Product life reference diagram/产品寿命参考图


Case Temperature 外壳温度 (tc)	50°C	60°C	65°C	70°C	75°C	80°C	85°C	90°C
Lifespan/寿命 (KHours)	120	120	120	91.9	64.9	45.9	32.5	22.9



3. Dimming function/调光功能

0-10V Dimming/0-10V 调光; 0, 5-100% dimming scope/调光范围 0, 5-100%


Dimming Voltage 调光电压 (V)	0	1	2	3	4	5	6	7	8	9	10	OPEN
Percentage of rated current 额定电流百分比	0%	0%	20%	33%	46%	58%	71%	84%	97%	100%	100%	95%-105%




4. Enclosure/外观示意图



5. Mounting hole size/安装孔尺寸





6. Label schematic / 标签示意图




7. Packing/包装

Net Weight/净重: 475g/475克



QTY/数量: 40pcs/40个

Carton Dimension/包装尺寸: 420x320x190mm

Net Weight/Gross Weight 净重/毛重: 19kgs/19.51kgs



两侧侧唛



两侧正唛

P/N:	LOT/NO:
QTY: PCS	DATE:
N. W: KG	G. W: KG
SIZE:	

History/历史

NO. 序号	DATE 日期	REVISION 版本号	REMARK 备注	Changer 修改人
1.	2018-07-06	V0.90	变更线材铭牌标准	陈绍勇/ Shaoyong Chen
2.	2018-08-15	V1.0	更改完善图表/Change the perfect chart	陈绍勇/ Shaoyong Chen
3.	2019-7-18	V1.1	更新标签信息, 增加FCC/Update label information and increase FCC	李克站/ Kezhan Li