



Exterior Wood Oil is to be used outdoors for basic treatment and maintenance of new and previously oiled wood surfaces such as decks, garden furniture, cladding etc. The special water-based composition of oil components ensures that the product is water-dilutable and friendly to the environment. The oil enhances the natural colour and grain of wood. Exterior Wood Oil Natural is recommended to enhance the natural colour structure of the wood. For rejuvenating of old wood surfaces, the pigmented oils are ideal as they recreate the original colour of the wood. A change of colour of the deck is also possible by applying e.g. the grey, anthracite or black oil.

- **Provides a hard-wearing surface**
- **May be used on all wood species, especially Exotic woods**
- **Contains UV protection**
- **Fast drying non film forming**
- **The coating resists mildew and UV damage**



## AppArea

Exterior Wood Oil is to be used outdoor for basic treatment and maintenance of new and previously oiled wood surfaces such as decks, garden furniture, cladding etc. May be used on traditional wood species such as pine and larch and on exotic species such as teak, mahogany, and ipé.

## Work\_Descrip\_Label

**Preparation\_Label** Clean new wood surfaces as well as old surfaces with WOCA Exterior Wood Cleaner before starting the oil treatment. Then leave the wood to dry for at least 24 hours so that the moisture content is not above 17%. Sand down any rough wood fibres with sandpaper, grit 120. Make the application in dry weather only, min. temp. 55°F. Avoid direct sunlight and high temperatures. Non pressure-treated softwood (except from red cedar) must be primed with the WOCA Exterior Wood Primer.

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

**Treatment** Stir the oil thoroughly before use. Apply an even and thin coat of oil with a brush or an Oil Applicator. Treat the end grain wood first. The wet oil may have a white shade. When the water has evaporated after a few minutes, the wood will appear oiled. Wipe off any excess oil with clean cotton cloths after no more than 5 minutes. Take particular care of removing excess oil from joints and grooves. If the surface does not appear saturated with oil, repeat steps. When the wood is dry, it may be polished with a polishing pad or polishing machine to ensure an extra hard-wearing surface.

**NoteTxt** Please note that Exterior Wood Oil in the black, anthracite and walnut colour are recommended to be finished with a coat of Exterior Wood Oil Natural to avoid excess colour coming off (for furniture).

## DryingTime

**FullyHard** 1-2 days



### Techdata\_label

---

Density	0.98 to 1.1 g/cm <sup>3</sup>
ShelfLife	36M
Viscosity	23 to 32 DIN CUP 4
Consumption	8-10 m <sup>2</sup> /L
Colours	Various colors
CleaningTools	Use water
Storage	+50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer (max. +77°F).
VOC Max	VOC-Max: 55 g/l.
AvailPotSizes	84.54 fl.oz. (2.5 L)
NonSlip	R10
Re-treatment	Repeat the oil treatment when required. Start cleaning the surface with WOCA Exterior Wood Cleaner.

### MaintenanceProd

---

DeepCleanProd	Exterior Wood Cleaner
RelatedProducts	Exterior Wood Primer

### Contact\_Label

---

WOCA Denmark A/S  
Tvæervej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*Disclaimer\_Long*