



Use Maintenance Oil Diamond Active for the ultimate care and maintenance of your oiled wood floor. This exclusive, low-odour, extremely tough maintenance oil is made from the absolute highest quality raw materials, to benefit both you and your oiled floor. In addition to being very easy to use and assuring minimal product waste, the maintenance oil refreshes the natural, warm glow of the wood and increases resistance to stains, via a unique hyper cross linking technology. Maintenance Oil Diamond Active is suitable for both manual and machine application to oiled floors.

- **Resistant to liquids such as water, coffee, tea and red wine**
- **Resistant to scratches and marks**
- **Gives the wood a beautiful, breathable surface**
- **IBR-certified**



AppArea

For oiled surfaces.

Work_Descrip_Label

Preparation_Label	<p>It is important that the product, the room and the floor are at a temperature between 59-86°F and that air humidity is approx. 50 %. Wood humidity must not exceed 12 %. Make sure that the room is well-ventilated for optimal evaporatio and drying time.</p> <p>The surface must be free of grime, grease and wax. Wash the floor with WOCA Intensive Wood Cleaner and leave the floor to dry for a least 8 hours or until it is completely dry.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Shake the container well. Apply approx. 3 fl. oz. of Maintenance Oil Diamond Active per 45 sq. ft. floor using a pad, short-bristled paint roller (1/4") or a buffing machine with a white pad on slightly larger areas. Make sure that the oil is polished well into the wood. Continue polishing until the wood seems saturated and the surface has an even, uniform appearance. Remove excess oil with clean, lint-free cotton cloths, before proceeding to the next section. The surface should not appear wet and no excess oil should remain on the surface. Continue, following the aforementioned method, until the whole floor has been treated.</p> <p>If the floor is polished with a buffing machine, it can be used with caution after 4 hours of drying time at 20°C. If polished manually, the floor can be used with caution after approximately 24 hours.</p>
NoteTxt	<p>Do not expose the floor to water or clean it for the first 3 days, while the oil is hardening.</p>

DryingTime

DryMachinePolis	4 hours at 68°F.
DryManualPolish	24 hours at 68°F.
FullyHard	3 days at 20°C
Rec	Do not expose the floor to water or clean it for the first 3 days, while the oil is hardening.



Techdata_label

Declaration	Drying oils.
Density	0.90 g/ml
SolidContent	Approx. 70 %
ShelfLife	36M
AppTemp	+15-30°C
Consumption	40-50 m ² /L, depending on wood type and surface
Colours	Natural and White
CleaningTools	Use WOCA Solvent or turpentine
Storage	+50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer (max. +77°F).
VOC Max	VOC-Max: 20 g/l.
AvailPotSizes	84.54 fl. oz.

MaintenanceProd

WeeklyCleanProd	Natural Soap
MonthlyCareProd	Oil Refreshing Soap
ReOilingProduct	Diamond Oil Active
RelatedProducts	Intensive Wood Cleaner

Contact_Label

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

Disclaimer_Long