

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Safranin O Stain

SYNONYMS: Safranin O Counterstain, Gram's safranin solution

CATALOG CODES: VGC

MANUFACTURER: Volu-Sol

ADDRESS: 5095 West 2100 South
Salt Lake City, UT 84120

EMERGENCY PHONE: (800) 535-5053

OTHER CALLS: (801) 974-9474

FAX: (801) 974-9553

CHEMICAL FAMILY: -

CHEMICAL FORMULA: -

PREPARED BY: Volu-Sol

RECOMMENDED USE: Laboratory chemical


RESTRICTIONS ON USE: Use as recommended

SECTION 2: HAZARD(S) IDENTIFICATION

EMERGENCY OVERVIEW:

GHS Classification: Flammable Liquids (Category 3)

GHS LABEL ELEMENTS:

Pictogram: 

Signal Word: Warning

Hazard Statement(s):
H226 Flammable liquid and vapour

Precautionary Statement(s):
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment
P242 Use only non-sparking tools
P243 Take precautionary measures against static discharge
P280 Wear protective gloves/ eye protection/ face protection
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction
P403+P235 Store in a well-ventilated place. Keep cool
P501 Dispose of contents/container to an approved waste disposal plant

OTHER HAZARDS: -

HMIS Classification:

Health hazard: 2

Chronic health hazard: -

Flammability: 2

Physical hazards: 0

NFPA Rating:

Health hazard: 2

Fire: 2

Reactivity Hazard: 0

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO. EC-NO. Index-NO.
Ethanol (10-20%)	64-17-5 200-578-6 603-002-00-5

SECTION 4: FIRST AID MEASURES

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Consult a physician

INGESTION: If swallowed, vomiting may occur spontaneously, but DO NOT INDUCE. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician

SKIN: Wash off with plenty of soap and water. Consult a physician

EYE: Rinse thoroughly with plenty of water for at least 15 minutes. Consult a physician

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR: Percentage by Volume
Upper: -%
Lower: -%

FLASH POINT: -

AUTOIGNITION TEMPERATURE: -

EXTINGUISHING MEDIA: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide

FIRE FIGHTING PROCEDURES: In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode

FIRE AND EXPLOSION HAZARDS: Use water spray to cool unopened containers

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: Use personal protective equipment. Avoid breathing vapours, mist, or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations. Dispose of in accordance with local regulations. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The number to contact the US Coast Guard National Response Center is (800) 424-8802

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Containers of this material may be hazardous when empty since they retain product residues (vapours, liquid); observe all warnings and precautions listed for the product. Take measures to prevent the buildup of electrostatic charge. No smoking

INCOMPATIBILITIES: -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMITS: Reported in a time-weighted average (TWA)

Component	CAS-No.	Reference	OSHA		ACGIH	
			ppm	mg/m ³	ppm	mg/m ³
Ethanol	64-17-5		1,000	1,900	1,000	1,900
			PEL	PEL	TLV	TLV

VENTILATION SYSTEM: Local and/or general exhaust is recommended to keep exposure below limits. Local exhaust ventilation is preferred for control of the emissions at its source, preventing dispersion into the general work area. Please refer to the ACGIH document, *Industrial Ventilation: A Manual of Recommended Practices*, for details

PERSONAL RESPIRATORS: If exposure limit is exceeded and engineering controls are not feasible, a half-face organic vapour respirator may be worn for up to ten times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier; whichever is lowest. A full-face piece organic vapour respirator may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not

known, use a full-face, positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres

SKIN PROTECTION: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands

EYE PROTECTION: Use chemical safety goggles and/or a full face shield where splashing is possible. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU). Maintain eye wash fountain and quick-drench facilities in work area

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: liquid
ODOR: -
SOLUBILITY: -
pH: -
BOILING POINT: -
MELTING POINT: -
VAPOR PRESSURE: -
SPECIFIC GRAVITY: -
MOLECULAR WEIGHT: -
DENSITY: -
VISCOSITY: -
REFRACTIVE INDEX: -

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable under recommended conditions of use and storage
CONDITIONS TO AVOID: Heat, flames, ignition sources
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: No data available

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:
Acute Toxicity: No data available
Skin/Eye Irritation: No data available
Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen
ROUTES OF ENTRY: Inhalation/Ingestion/Skin

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:
Toxicity: No data available
Persistence and degradability:
Mobility in soil: No data available
PBT/vPvB Results: PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is flammable. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in an RCRA approved waste facility. Processing, use, or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state, and local requirements. Dispose of as unused product

SECTION 14: TRANSPORT INFORMATION

US DOT	IATA	IMDG/IMO
Shipping Name: Ethanol Solution	Shipping Name: Ethanol Solution	Shipping Name: Ethanol Solution
Hazard Class: 3	Hazard Class: 3	Hazard Class: 3
UN Number: 1170	UN Number: 1170	UN Number: 1170
Packing Group: III	Packing Group: III	Packing Group: III

SECTION 15: REGULATORY INFORMATION

SARA 302	-
SARA 313	-
SARA 311/312 Hazards	Fire hazard, Acute Health Hazard, Chronic Health Hazard
State	Right to know lists: MA: 64-17-5 PA: 64-17-5, 7732-18-5 NJ: 64-17-5, 7732-18-5 California Prop. 65 Components:

SECTION 16: OTHER INFORMATION

Disclaimer: The information is provided without any representation or warranty, express or implied, regarding the accuracy or correctness. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of the product.