Polaris RZR 170 Installation Guide

Fitment: RZR 170 (All Years)

PARTS INCLUDED

8- M6 nuts 4 - Square Brackets

8-1/4 Flat Washers 8 - Carriage Bolts

4 - Spacers 8-5/16-18 Nuts 8 - Washers 2- RZR 170 Seats

TO INSURE YOUR SAFETY AND THE SAFETY OF OTHERS AND AVOID PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND NOTES REGARDING THE USE AND CARE OF THIS PRODUCT

STEP 1: Remove the stock RZR 170 Seats. To remove the driver seat, pull the slider lever and slide the seat all the way forwards and it will slide out. To remove the passenger seat, remove the two bolts on the front of the seat using a 12mm wrench.

STEP 2: Remove the square mounting plates on the stock seats by unscrewing the 4 M6 bolts on both seats. The driver seat will have the sliding mechanism. Make sure to keep the same parts together.

STEP 3: Mount the square tubes to the stock mounting bracket that you removed in step 2. Make sure that the taller side of the square tube is facing towards the front. Use the factory m6 bolt and the included nuts and washers to mount the tubes to the mounting bracket.

▲ WARNING:

This product can expose you to chemicals, which are known to the State of California to cause cancer. For more information, visit www.P65Warnings.ca.gov.

STEP 4: Mount the square tubes and the stock mounting plate to your new RZR 170 seats. Use the included carriage bolts, washers, nuts, and spacers to do so. Measure the spacing from the mounting brackets in the RZR 170 and space accordingly. The spacer should be used in the front of the seat (Figure 1)



Driver

figure 1

Passenger

STEP 5: Mount the seats back into the RZR 170 the same way that you removed them in step 1.

TIP: If you need to lower the driver seat you can mount the seat directly to the stock slider bracket without the square tubes. This only applies to the driver side.

Warning

RACING IS DANGEROUS. INCIDENTS WILL OCCUR RESULTING IN INJURY AND DEATH. IN BEST CONDITIONS THIS PRODUCT MAY LIMIT TRAUMA. THIS PRODUCT WILL NOT PREVENT TRAUMA ASSOCIATED WITH RACING INCIDENTS. ONLY INSTALL OR USE THIS PRODUCT WITH THE GUIDANCE OF THE PRODUCT WITH THE GUIDANCE OF THE ANCE OF A
CERTIFIED ENGINEER OR THE
USERS SANCTIONING ORANIZATION. REPLACE THIS PRODUCT
AFTER ANY CRASH, FIRE OR ANY
EVIDENCE OF WAR TO ANY OF ITS
MATERIALS OR COMPONENTS.
USER IS RESPONSIBLE TO EVIDENCE OF WEAR TO ANY OF ITS MATERIALS OR COMPONENTS. USER IS RESPONSIBLE TO INSPECT THIS PRODUCT BEFORE EVERY USE. THIS PRODUCT IS DISTRIBUTED WITHOUT ANY WARRANTY. ACES RACING IS NOT LIABLE FOR ANY INCIDENTS

WARNING

It is the users responsibility to comply with local laws and regulations. This product shall be used for off-highway use only.

Aces-Racing.com