

CS190

GRITTY PRIMER



KEY BENEFITS SUMMARY

- Provides an excellent key and extra grip surface
- Rapid drying – in as little as 15 minutes
- Designed for use on a wide range of absorbent and non-absorbent surfaces
- Ready mixed and ready to use; apply straight from the re-sealable tub
- Significantly improves adhesion and bond strength of tile adhesives and smoothing compounds

PRODUCT INFORMATION

Description

CS190 Gritty Primer is a ready mixed, ready to use rapid drying primer that can be used on both absorbent and non-absorbent substrates. CS190 provides a textured surface which gives an excellent bonding surface for self-levelling/smoothing compounds and screeds.

Usage / Purpose

CS190 Gritty Primer is suitable for use on a wide range of substrates including existing ceramic, porcelain and natural stone tiles, existing vinyl flooring, flooring grade asphalt and bitumen, epoxy DPMS, plaster, metal, fibreglass, concrete, sand/cement screed, timber substrates and under floor heating systems.

Packaging

5 kg re-sealable tub

Colour

Green

Availability

Direct from Tremco CPG UK Limited (see back of leaflet for address and telephone details).

Standards

All aspects of the installation must be in accordance with the requirements of BS 8203 & BS 8204 and supplementary specifications.

Moisture Testing

Suitable for application to substrates with moisture content <75% RH. For substrates with moisture content above these levels, ensure the substrate has a suitable intact damp proof membrane.

Protective Equipment

Use in well ventilated conditions and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

Preparation

All substrates must be clean, dry and free from dust, dirt, oil, grease and other contaminants that may affect adhesion. Substrate and ambient temperature must be above 5°C.

Application Instructions

- Shake or stir CS190 before application to ensure equal dispersion of the aggregate component. Apply a thin, even coat using brush or roller ensuring 100% coverage. Do not over apply as this can cause CS190 to skin over.
- Once applied, allow CS190 to become touch dry before applying further surface dressing. This will take between 15-60 minutes depending on the ambient temperature and the porosity of the substrate. Higher temperatures and porous substrates will reduce curing time while lower temperatures and non-porous substrates will increase curing time of CS190.
- Once applied, avoid trafficking the primed area.
- Reseal the container after use to prevent evaporation and possible contamination of CS190.

Cleaning

Wash tools immediately after use with warm water.

CS190

GRITTY PRIMER

TREMCO

Health & Safety Precautions

Safety data sheet must be read and understood before use.

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

Tremco CPG UK Limited Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

TECHNICAL DATA

PROPERTY	RESULT
Composition	A proprietary mixture of inorganic fillers and a unique acrylic binder with adhesion promoters, rheology modifiers and other functional additives
Cure Time	15-60 minutes depending on ambient temperature and porosity of substrate
Coverage	Approximately 45-65 m ² depending on porosity of substrate and ambient temperature
Application Temperature	Minimum +5°C
Storage	Store in cool, dry and frost-free conditions
Shelf Life	12 months when stored as recommended in original unopened containers



Tremco CPG UK Limited
Coupland Rd, Hindley Green, Wigan WN2 4HT
United Kingdom
Tel: +44 (0)1942 251400
Email: info.UK@cpgeurope.com

 Construction Products Group Europe
www.cpg-europe.com

2021-03