GENIEMAT® FF05NP





PRODUCT SPECIFICATION	
Product Name:	GenieMat FFo5NP Sheets
Description:	Robust sound transmission mat made from 94% recycled rubber content. Designed to reduce the transmission of impact sound generated by footfall noise for various types of structures for both residential and commercial use.
Features and Benefits:	 Tested by 3rd party accredited laboratories to significantly reduce impact sound Mold, bacteria, fungi, and water resistant Qualifies for LEED® points Easy to install and rolls out quickly Will not fail under high point loads
DIMENSION:	Sheet: 1.22 m x 2.13 m
THICKNESS:	nom. 4.5 mm \pm 0.5 mm (tolerances are pursuant to ISO 3302-1).
SHEET WEIGHT:	$\geq 9.75 \text{ kg/sheet} - 3.75 \text{ kg/m}^2$
SHEET AREA:	2.60 m²/sheet
SHEETS/PALLET:	95
TECHNICAL DATA	
Tensile Strength & Elongation at Break: (ASTM D412)	≥ 0.7 Mpa ≥ 65%
Type A Hardness (ASTM D2240):	40 durometer
REDUCTION OF IMPACT SOUND PRESSURE LEVEL:	ΔLw 25 dB (ISO 717-2)
TEMPERATURE STABILITY:	-40°C to +115°C (-40°F to +240°F)

CONTACT US

For Your Project Specific Questions

Middle East +971 4 813 5501 | **UK** +44 203 9846444 | **Asia Pacific** +65 8452 6865 **E.** info@pliteq.ae





