

Video/Surveillance

V300 Video Streaming Hard Drive

Stream. Record. Edit.



3 2 1
TB TB TB

Color ●

Toshiba's 3.5-inch V300 Video Streaming Hard Drive with up to 3 TB lets you stream, record, edit and play video content on DVR, TV or NVR – with all the efficiency and reliability you need. A 64 MB buffer helps deliver smooth performance, while temperature control technology limits heat buildup, extending service life for added reliability. A drive that's quiet and more efficient than ever, thanks to Toshiba's Silent Seek Technology, and reduced energy consumption.

Use for:

- Video Editing Systems
- Set-Top-Box (STB)
- Digital Video Recorders (DVR)
- Network Video Recorders (NVR)
- Video Surveillance Systems




- ? 3.5" SATA Hard Drive
- ? 64 MB buffer
- ? 24/7 operation
- ? Up to 16 cameras
- ? Toshiba Silent Seek Technology
- ? Temperature control

Manual

[Installation-and-Safety-Internal-HDDs.pdf](#) ?



Product Specifications



Basic Specifications

Form factor	3.5-inch
Interface	6.0 Gbit/s
Number of cameras supported	16
Drive bays supported	up to 8
Advanced Format (AF)	Yes
RoHS compatible	Yes
Halogen Free	Yes
Shock Sensor	Yes

Performance

Rotational speed	5940 rpm (3 TB), 5700 rpm (1 TB - 2 TB)
Buffer size	64 MB
Native Command Queing (NCQ)	supported

Reliability

Workloads	72TB/year
Unrecoverable error rate	1 per 10E14 bits read
24/7 operation	Yes
Load / Unload Cycle	300,000

Power Management

Supply voltage	5VDC (±5%) / 12VDC (±10%)
----------------	---------------------------

Box Content

Box Content	3.5-inch internal HDD - V300 Video Streaming Hard Drive
-------------	---

Physical

Weight (approx.)	700 g max. (2 TB, 3 TB), 450 g max. (1 TB)
Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm

Environmental

Acoustics (idle mode)	24 dB typ. (3 TB), 22 dB typ. (2 TB), 19 dB typ. (1 TB)
Shock (non-operating)	300 G / 2 ms half sine
Shock (operating)	70 G / 2 ms duration
Vibration (non-operating)	1.04 G (2 to 200Hz)
Vibration (operating)	0.67 G (5 to 500 Hz)
Temperature (operating / non-operating)	0 to 65° C / -40 to 70° C

Power Management

Consumption - Active Idle	4.20 W typ. (3 TB), 3.30 W typ. (2 TB), 3.00 W typ. (1 TB)
---------------------------	--

Product Range

Part number	Capacity	Color
HDWU130UZSVA (Bulk)	3 TB	-
HDWU120UZSVA (Bulk)	2 TB	-
HDWU110UZSVA (Bulk)	1 TB	-

Logistical Information:

Box dimensions	n/A
Box weight (gross)	n/A
Master carton dimensions	321 x 406 x 213 mm
Master carton weight (gross)	16 kg (typ.), 11 kg (typ.) (1TB)
Boxes per master carton	20
Pallet dimensions	n/A
Pallet weight (net)	n/A
Units per pallet	720

Contact

Toshiba Electronics Europe GmbH

Hansaallee 181
40549 Düsseldorf
Germany