



TL-D1600S

Drive Bay	12 x 3.5-inch SATA 6Gb/s, 3Gb/s + 4 x 2.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	<p>3.5-inch bays:</p> <ul style="list-style-type: none"> 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives <p>2.5-inch bays:</p> <ul style="list-style-type: none"> 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Audio Alert On/Off Switch	Yes
Form Factor	Tower
Host Interface	4 x SFF-8088
LED Indicators	HDD 1-16, Status, Link, Fan error
LCD Display/ Button	Yes
Buttons	Power switch
Dimensions (HxWxD)	303.84 × 369.89 × 319.8 mm
Weight (Net)	11.59 kg
Max. number of HDDs/SSDs supported	16
Hard Drive Type	<p>3.5-inch SATA hard disk drives</p> <p>2.5-inch SATA hard disk drives (for 3.5-inch tray slots only)</p> <p>2.5-inch SATA solid state drives</p>
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	250W PSU, 100 - 240V
Power Consumption: Operating Mode, Typical	93.66 W
Fan Mode Switch	Yes (Auto, high, medium, low)

Fan	3 x 92mm, 12VDC
System Warning	Buzzer
Kensington Security Slot	Yes

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.