



TL-D400S

Drive Bay	4 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Audio Alert On/Off Switch	Yes
Form Factor	Tower
Host Interface	1 x SFF-8088
LED Indicators	HDD 1-4, Status, Link, Fan error
Buttons	Power switch
Dimensions (HxWxD)	168.5 × 160.2 × 219 mm
Weight (Net)	3.66 kg
Max. number of HDDs/SSDs supported	4
Hard Drive Type	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	65W adapter, 100 - 240V
Power Consumption: Operating Mode, Typical	22.985 W
Fan Mode Switch	Yes (Auto, high, medium, low)
Fan	1 x 120mm, 12VDC
System Warning	Buzzer
Kensington Security Slot	Yes

Note: Use anly ONIAD memory medules to maintain system nerformance and stability. Ear NIAC devises with more than ano memory

Note: Use only QINAP memory modules to maintain system performance and stability. For INAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting. Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.